



+  [View More](#)

PRODUCT NUMBER: IHR540

IHR 540

Intended to grasp and move hot parts quickly in the metallurgy, aluminium and glass industries.

Honeywell

Overview

Reference Number

IHR540

Product Type

Gloves

Range

Thermal Protection

Line

Heat

Brand

Honeywell

Brand formerly known as

SPERIAN

Industry

- ☒ Industry
- ☒ Automotive and Part Manufacturer
- ☒ Foundry
- ☒ Glass Industries
- ☒ Iron and steel industry

Product Use

Intended to grasp and move hot parts quickly in the metallurgy, aluminium and glass industries.

Features & Benefits

Feature

5-finger-glove in rubber and silicon coated fabric
 Felt Kevlar® lining in addition with glass fabric between two layers
 Cuff 20 cm (+/-1 cm) in aluminised glass fabric
 Ambidextrous

Benefit

COMFORT

5-finger glove for a better grip on hot objects and added dexterity.

RESISTANCE

The alternating Kevlar and glass fabric offer excellent insulation with respect to the contact temperature (withstanding 900°C for up to 20 seconds) and good protection against splashes of molten metal.

The blend of both materials is a good substitute for asbestos.

SAFETY

The aluminised glass fabric cuff protects a large part of the forearm.

Technical Description

Description

CE CATEGORY : II Intermediary risks

In accordance with standards :

EN 420-94 EEC Basic standards

EN 388-94 Mechanical risks

EN 407-94 Thermal risks

CHARACTERISTICS :

Glove in rubber and silicon coated fabric

Felt Kevlar® lining in addition with glass fabric between two layers

Cuff 20 cm (+/-1 cm) in aluminised glass fabric

Ambidextrous

Product Technology

Cut and Sewn

Coating Type

Glass fabric and Kevlar®

Length

40 cm

Harmlessness

In conformity with the European standards

Sizes

Unique size

EN 407 - Heat and/or Fire

Behaviour and/or fire	4
Resistance to contact heat	4
Resistance to convective heat	X

Resistance to radiant heat	X
Resistance to small metal splashes	3
Resistance to molten metal splashes	4

EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	2
Cutting resistance	0
Tear resistance	4
Puncture resistance	0

Packaging Label

Tagging

CE SPERIAN

IHR540 XX

EN 420

EN 388 : 2040

EN 407 : 44XX34

Certifications

E.C. Declaration of Conformity

EC Category PPE

2

EC Certificate Number

0

EC Attestation

 EC Attestation

EC Attestation Number

03197009

Photos & Images

We're sorry, there are no images available at this time.

User Manual

UI 106

Additional Information

User Information Sheet

106

Maintenance

Storage Information

Minimum packaging 5 pairs.

Cartons of 50 pairs.

Care Instructions

In order to keep its properties, this article should not be cleaned.