


# SQUALE

## OTG

SQUALE OTG provide excellent protection for wearers of prescription glasses.



SQUPSI



SQUPSJ



SQUWPCC5



43 g

SUPPLIED WITH

Cord  
CORD



- + UPPER PROTECTION
- + ADJUSTABLE TEMPLES
- + LOWER PROTECTION

**bolle**  
SAFETY

# SQUALE

OTG

| MODEL  | VERSIONS  | REFERENCES | LENS MARKING   | FRAME MARKING   | COATINGS              |
|--------|---|------------|--|---|-----------------------|
| SQUALE |  Clear           | SQUPSI     | 2C-1,2  1 FT €€ |  EN166 FT €€ | Anti-scratch/anti-fog |
|        |  Yellow          | SQUPSJ     | 2C-1,2  1 FT €€ |  EN166 FT €€ | Anti-scratch/anti-fog |
|        |  Welding shade 5 | SQUWPCC5   | 5  1 S €€       |  EN166 S €€  | Anti-scratch          |

## LENS MARKING

### Optical class symbols:

1. Continuous work

### Mechanical strength symbols:

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

**S.** Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s

### Others symbols:

€€ European standard  Manufacturer name

## FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

**S.** Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s

€€ European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

| PACKAGING AND EAN13 CODE             |               |               |               |
|--------------------------------------|---------------|---------------|---------------|
|                                      | SQUPSI        | SQUPSJ        | SQUWPCC5      |
| Individual plastic bag               | 3660740003203 | 3660740003517 | 3660740002343 |
| 10 safety spectacles per inner box   | 3660740103200 | 3660740103514 | 3660740102340 |
| 180 safety spectacles per outer pack | 3660740203207 | 3660740203511 | 3660740202347 |

| CHARACTERISTICS |                       |
|-----------------|-----------------------|
| LENSES          | PC - 2,0 mm - Curve 4 |
| FRAME           | PC                    |
| TEMPLES         | PC + Nylon            |
| STRAP           | Non applicable        |
| FOAM            | Non applicable        |
| SPARE LENSES    | No                    |



01/10/2013

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

[bolle-safety.com](http://bolle-safety.com)

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY