



TECHNICAL DATASHEET

REFERENCE : **E3560-002**

Old référence :

Description :

Made of 100% cotton 340g / m2 flame retardant treated Proban® - with neckband.

exists with or without a neckband and with or without a visor.

Model with neck protector and without visor - green

Dimensions :

Sizes available Unique


Protection of the head and neck against flames and splashes of small incandescent particles.

Recommandation

The materials of this article do not contain any substance that can harm the health of the user

This PPE is in conformity with the requirements of the Directive 89/686/CEE.
has been the subject of the 033/2017/0382 CENTEXBEL

The CE marking on these items means the respect for the essentials requirements of European Directive on PPE based on the standard ISO 13688



A1 B1 C1 D0 E1 F0

ISO 11612+11611

A Limited flame spread (1 à 3)
B Convective Heat (1 à 4)
C Radiant Heat (1 à 4)
D Projection of molten aluminium (1 à 3)
E Projection of molten iron (1 à 3)
F Contact Heat (1 à 3)

Use only within the risks covered above


Maintenance :



A dirty clothe may cause a reduced protection/ At the wash, at the place of projections, the black crust that has protected the skin can jump and make a hole in the garment

Storage : Protected from the light and in a dry place, free of moisture, oils, greases...

Recommandation : not suitable for molten aluminum - this equipment must be completed with flame retardant EPI



Coat/Apron

Lenght	A	Sizes	B et C
120 cm	164-170 cm	S – T2	92-96 cm
130 cm	170-182 cm	M – T3	96-104 cm
140 cm	182-188 cm	L – T4	104-112 cm
150 cm	188-194 cm	XL – T5	112-120 cm
160 cm	194-200 cm	XXL – T6	120-128 cm

For coveralls, take the greatest size between **B** or **C**.
The measures must be taken on the person wearing his work clothes, because this equipment is worn over.
In doubt between two sizes choose the larger one.