



TEGERA® 19

Welding and heat-resistant glove, fully lined, 1,2-1,4 mm split cowhide of top quality, jersey, Cat. II, yellow, withstands contact heat up to 100°C, reinforced seams, elasticated 180°, for heavy work

PROPERTIES

High level of protection, good fingertip sensitivity, very durable, good fit

SPECIFICATION

TYPE OF GLOVE Welding gloves

CATEGORY Cat. II

SIZE RANGE (EU) 8, 9, 10, 11

PALM MATERIAL Split cowhide of top quality

PALM THICKNESS 1,2-1,4 mm

BACK MATERIAL Split cowhide of top quality

LINING Fully lined

LINING MATERIAL Jersey

DEXTERITY 1

CUFF STYLE Extended safety cuff

CUFF MATERIAL Leather

FASTENING Elasticated 180°

LENGTH RANGE 310-360 mm

COLOUR Yellow

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY No thread

OUTER MATERIAL SPECIFICATION Leather, natural latex

INNER MATERIAL SPECIFICATION Cotton

SIZE	ART. NO.	EAN NO.
10	19-10	7392626001992
11	19-11	7392626027473
8	19-8	7392626072299
9	19-9	7340118300948

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 19

FEATURES

Withstands contact heat up to 100°C, reinforced seams, flame retardant, withstands welding sparks and grinding splash

PREVENTS RISK OF

Burn injuries, heat injuries, abrasion injuries, blisters, grazes, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Warm environments, harsh environments

PRIMARY AREAS OF USE

Engineering, hot work, mining

PRIMARY INDUSTRIES OF USE

Mining, metal fabrication, automotive

TYPE OF WORK

Heavy weight

2(3)



CE Cat. II

EN 420:2003 + A1:2009



EN 388:2016
3143X



EN 407:2004
41314X

EN 12477:2001 + A1:2005

Type A

EN 1149-2:1997
R:26,138x10°Ω



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-04-15

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 19

EU-TYPE EXAMINATION

0321 SATRA Technology Centre, Wyndham Way, Telford Way,
Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general
requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	3	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat
and/or fire)

EN 12477:2001 + A1:2005 Protective gloves for welders

Type A - Lower dexterity (with higher other performance)

EN 1149-2:1997 Electrostatic properties (vertical
resistance)



CE Cat. II

EN 420:2003 + A1:2009  EN 388:2016 3143X  EN 407:2004 41314X

EN 12477:2001 + A1:2005 Type A EN 1149-2:1997 R:26,138x10°Ω 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-04-15

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com