



TEGERA® 321

Synthetic leather glove, unlined, 0,6 mm synthetic leather, polyester, Cat. II, black, grey, reinforced index finger, chrome free, elasticated 180°, for fine assembly work

PROPERTIES

Good fingertip sensitivity, flexible, comfortable

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE 6, 7, 8, 9, 10, 11

PALM MATERIAL Synthetic leather

PALM THICKNESS 0,6 mm

BACK MATERIAL Polyester

LINING Unlined

DEXTERITY 5

FASTENING Elasticated 180°

LENGTH RANGE 220-260 mm

COLOUR Black, grey

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Hook with hangtag

MATERIAL SPECIFICATION Polyurethane, polyester

SIZE	ART. NO.	EAN NO.
6	321-6	7392626069169
7	321-7	7392626056077
8	321-8	7392626056107
9	321-9	7392626056138
10	321-10	7392626056169
11	321-11	7392626056190

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 321

FEATURES

Chrome free, reinforced index finger, short model

PRIMARY PROTECTION

Prevents risk of, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping

PRIMARY ENVIRONMENTS OF USE

Dry environments

PRIMARY AREAS OF USE

Fine assembly, assembly, inspection work, machine operating, installation work, HVAC installation, machine driving, warehouse work

PRIMARY INDUSTRIES OF USE

Automotive, transportation, utilities, logistics, HoReCa, facilities, service, retail

TYPE OF WORK

Light weight

2(3)



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-03-13

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com



CE Cat. II



TEGERA® 321

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

Council directive 89/686/EEC (PPE Directive)

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to wear (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection	1	2	3	4	5
A) Resistance to wear (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-03-13