



TEGERA® 48

Chemical protection glove, 0,60 mm nitrile, diamond grip pattern, unflocked, Cat. III, green, extra long, latex-free, for allround work

PROPERTIES

Highest level of protection, very durable, good grip, good fit, comfortable

SPECIFICATION

TYPE OF GLOVE Disposable and/or chemical resistant gloves

CATEGORY Cat. III

SIZE RANGE (EU) 8, 9, 10, 11

MATERIAL Nitrile

THICKNESS 0,60 mm

INSIDE Unflocked

GRIP PATTERN Diamond grip pattern

LENGTH RANGE 450 mm

COLOUR Green

PAIRS PER PACKAGE/CARTON 6/36

AQL 0.65

DISPLAY Bag

SIZE	ART. NO.	EAN NO.
8	48-8	7392626038745
9	48-9	7392626038752
10	48-10	7392626038769
11	48-11	7392626038776

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 48

FEATURES

Protection against chemicals, approved for handling foodstuffs, extra long, latex-free

PREVENTS RISK OF

Risk of infection, corrosive injuries, contact with dirt, contact with chemicals, contact with moisture, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Agricultural work, petro-chemical work, chemical work, chemical technology work, laboratory work, paint spraying work, paper industry work, decontamination, sanitation, cleaning

PRIMARY INDUSTRIES OF USE

Agriculture, oil, gas, petrochemical, pulp and paper, chemical, rubber and plastic, metal fabrication

TYPE OF WORK

Medium weight

2(4)



CE 0321 Cat. III

EN 388:2003
4102

EN 374-2:2003

EN 374-3:2003
FKL



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-04-23

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 48

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

Council directive 89/686/EEC (PPE Directive)

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	4	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	0	(4)
D) Puncturing resistance (Newton)	2	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	




Suitable for contact with foodstuffs

EN 374-2:2003 Protective gloves against chemicals and micro-organisms - Part 2: Determination of resistance to penetration

EN 374-3:2003 Protective gloves against chemicals and micro-organisms - Part 3: Determination of resistance to permeation by chemicals



CE 0321 Cat. III



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-04-23

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 48

Permeation levels are based on breakthrough times as follows

Permeation level	1	2	3	4	5	6
Minimum breakthrough times (min)	10	30	60	120	240	480

Definition of breakthrough time through the glove palm (1ugm/cm²/min)

F: Toluene (CAS number 108-88-3) - Permeation level 2

K: Sodium hydroxide 40% (CAS number 1310-73-2) - Permeation level 6

L: Sulphuric acid 96% (CAS number 7664-93-9) - Permeation level 5



CE 0321 Cat. III

EN 388:2003
4102

EN 374-2:2003

EN 374-3:2003
FKL



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2019-04-23

4(4)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com