

Product Datasheet uvex 1 x-tended support 8516.1-3 S3 SRC**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth****Product information**

- Sporty, multifunctional safety shoe
- Especially lightweight and flexible
- The latest generation of 100% metal-free uvex xenova® toe cap, compact design, anatomical shape, good side stability, no thermal conductivity and antimagnetic properties
- Penetration-resistant, non-metallic midsole in accordance with the latest safety standards, does not restrict flexibility
- Made with a new developed last technology for extended wearing comfort
- uvex climazone technology ensures optimum wearer comfort
- Breathable, water-resistant high-tech micro velour upper material
- Distance mesh lining provides optimum breathability
- Suitable for people allergic to chrome. Made from synthetic materials
- Comes with elastic laces for quick, individual adjustment
- Virtually seamless design to eliminate pressure points
- Removable comfort insole, antistatic, with moisture control system and additional shock absorption in the heel and at the front of the foot
- Soft, padded collar and tongue
- Medial and lateral heel support for the foot through an especially designed side frame to protect against

	ankle injuries, for guidance and impact protection • Fulfils ESD requirements: resistance to ground < 35 megohm • Certified with uvex medicare for individual, orthopaedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions																
Outsole	• Multi-layer-shock absorption system using dual density polyurethane for walking comfort • Self-cleaning tread optimised for slip resistance • Free of lacquer wetting inhibitors such as silicones, phthalates, etc. • Ideal shape around the joints for optimal torsion and good flexibility • Joint insert for climbing ladders securely • Pivot point eases turning when standing • High abrasion-resistant PU sections ensure secure stepping and rolling of the foot, which helps prevent accidents																
Technical data	<table><tr><td>Art.-no.</td><td>8516.1</td><td>.2</td><td>.3</td></tr><tr><td>Width</td><td>10</td><td>11</td><td>12</td></tr><tr><td>Standard</td><td colspan="3">EN ISO 20345:2011 S3 SRC</td></tr><tr><td>Size</td><td colspan="3">35 – 52</td></tr></table>	Art.-no.	8516.1	.2	.3	Width	10	11	12	Standard	EN ISO 20345:2011 S3 SRC			Size	35 – 52		
Art.-no.	8516.1	.2	.3														
Width	10	11	12														
Standard	EN ISO 20345:2011 S3 SRC																
Size	35 – 52																
Accessories	<i>uvex 1 comfortable climatic insole</i> (article no.: 9534.7-9) • Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones • Ultra breathable and moisture-absorbing materials • Shock absorption zones that assist natural movement • Non-irritating, comfortable surface structure <i>Laces</i> • Black (article no.: 9599.9 11) • Elastic laces (article no.: 9591.000)																