

JALARTHUR SAS JMI04

S1 P SRC
EN ISO 20345:2011
39 to 47



- Full grain leather
- **Dual density Softane™** sole
- Antistatic and non-magnetic

- ❖ Golfing brogue type shoe, black.
- ❖ Upper in finest quality water-resistant leather, 2,0 / 2.2 mm thick.
- ❖ Inner lining in full grain leather.
- ❖ Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- ❖ Tongue in finest quality leather, leather lined.
- ❖ Closure by black laces : 90 cm.
- ❖ **Ergonomic shoe**, with **broad synthetic polymer toecap**, for **saving on weight (50% lighter than steel)**. Impact resistance to **200 Joules**.
- ❖ **New manufacturing process**: inner sole and insert in **FlexTane™ By Jallatte** perforation resistant material, antistatic, **100% composite**. Sewn directly onto the bootstrap and covering **100% of the foot** for all-round protection.
- ❖ Removable inlay, covering the entire surface of the foot, antistatic, anatomical and with shock-absorbent heel. High ability to absorb and evaporate perspiration.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Sole in dual-material **Softane™** fitted with progressive effect shock absorber protecting the back and joints from vibrations.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011 **Requirement SRC (SRA+SRB)**

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,48** (>0,32) – On the heel **0,37** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,25** (>0,18) – On the heel: **0,16** (>0,13)

- ❖ Comfort layer, density = 0.45
- ❖ Wear layer, density = 1.10
- ❖ Heel shock absorber 27 Joules
- ❖ Very high level of resistance to oils and hydrocarbons
- ❖ Abrasion resistance 90 mm3

Weight	Gross weight (42) : 1325 g / Net weight (42) : 1020 g			
Size	35 to 39	40	41 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		340 x 210 x 133	
Cartons (mm)	590 x 210 x 320	590 x 410 x 320	685 x 440 x 359	685 x 225 x 359

