

TRIFTANE Tradition

JALCAMPO SAS
J0286

S3 HRO SRC
EN ISO 20345:2011
35 to 47



- Full grain leather
- **TRIFTANE™** sole

- ❖ Black sporty urban sport
- ❖ Water-repellent full grain waxed leather upper. Thickness 1.9/2.1 mm
- ❖ « 3D » inner lining, combining foam for comfort and protection and an open structure (mesh panel) that improves air flow around the foot.
- ❖ Heel stiffener to reinforce the heel seat
- ❖ Vamp lining in non-woven fabric. Resistant to scuffing and to acid perspiration
- ❖ Inlay supporting the entire surface of the foot, removable, antistatic, anti-bacteria treated, anatomically shaped to absorb heel impact. High ability to absorb and desorb perspiration.
- ❖ Patented 200 Joule safety toecap with perforations, 9th width,
- ❖ 200 Joule puncture resistant midsole (SAS)
- **Triftane™** sole technology with high slip resistance :

Excellent slip resistance

- Treads have sharp edges and are independent. The sole pattern corresponds to the pressure zones of the foot, optimising the contact surface with the ground

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic/lubricant :
water and detergent
On flat 0,57 (>0,32) – On the heel 0,56 (>0,28)

SRB Test ground steel/lubricant : glycerine
On flat 0,26 (>0,18) – On the heel: 0,35 (>0,13)

Abrasion resistance < 81mm3

- NBR shore hardness : 60
- The protective grid guarantees the boots' durability

Heel shock absorption : 28 joules

- Hollowed out centre area of heel helps absorb shock
- Softane™ comfort layer, density = 0,45

All purpose :

- Resistant to oils and hydrocarbons, and acids and bases at low concentrations
- Resistant to direct contact heat up to 300°C

Weight	Gross weight (42): 1400g / Net (42): 1130 gr												
Sizes	35	36	37	38	39	40	41	42	43	44	45	46	47
Packaging				5 pairs			10 pairs					5 pairs	
Dimensions (mm)				590x220x348			590x437x348					685x250x358	