



PHEBUS
05934

S3 HRO SRC
EN ISO 20345:2011
38 to 47

Safety boot



SPECIALS

- ☞ Safety boot. Specifically designed for foundry work.
- ☞ Black leather upper.
- ☞ Inner lining of the quarters in **AIR-LIGHT®** high respiration and rapid drying, colour grey.
- ☞ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ☞ Collar lined and padded with flexible foam for better ankle protection.
- ☞ Front of foot protected by leather bellows covered with a spark arrester flap.
- ☞ Stitching strengthened with rivets.
- ☞ Adjustable closure system with Velcro straps.
- ☞ Complete **VENTO-PLUS®** anatomical and antistatic inlay, with honeycomb structure for improved air circulation.
- ☞ Steel toecap offering protection from an impact of 200J.
- ☞ Stab-resistant steel liner.
- ☞ Antistatic shoe.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water
and detergent

On flat **0,41** (>0,32) – On the heel **0,32** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,21** (>0,18) – On the heel: **0,16** (>0,13)

Sole with ground contact layer in **Néotril™** / Softane comfort layer :

- ▶ Resistant to oil and hydrocarbons .
- ▶ Contact heat resistant up to 300°C.
- ▶ Deep self-cleaning treads.
- ▶ Absorbs impact to the heels > 20 Joules.

Weight	Gross weight (42): 1488 g / Net weight (42) : 1280 g		
Size	36 to 39	40 to 45	46 to 47
Packaging	5 pairs	10 pairs	5 pairs
Dimensions	700x255x360	700x510x360	700x255x360

