



LEMAITRE SECURITE SAS
17 rue Bitschhoffen
CS 90024
F 67350 La Walck FRANCE
Tél. : +33 (0)3 88 72 28 80
Fax : +33 (0)3 88 07 05 37
www.lemaitre-securite.com
info@lemaitre-securite.com



TECHNICAL FILE

UPDATMENT of the document : 28/032013
ISO reference of the document : DON/LS 03.996.C



CORINNE S2 SRC
BALLERINA-STYLE LINED LEATHER
SHOE WITH STRAP

PROTECTION FOR THIS MODEL



Sizes available from 35 (2) to 42 (8)
Weight of one pair in size 38 : 700 gr.
Norme EN ISO 20345 : 2011
AET : 0161/19543/10

Upper features

- Upper : Water repellent full grain leather
- Lining : leather
- Vamp lining : synthetic
- Counter : synderme
- Fastenning : strap with metallic buckle
- Marking: size, manufacturer, manufacture date (month, date), norm, protection, CE marking.

Protections

- Toecap : steel (200 joules)

Fitting features

- Natur'form (large)
- Lasting : California
- Lasting insole : textile
- Footbed : polyurethane

Sole features

- Name : PARABOLINE
- Material : double density polyurethane
- Comfort sole density : 0,5
- Color comfort sole : darkgrey
- Undermine sole density : 1
- Color undermine sole : black
- Slipping resistance SRA (flat) : 0,45 ; SRA (heel) : 0,56
- Slipping resistance SRB (flat) : 0,22 ; SRB (heel) : 0,16

Requirements of the norm EN ISO 20345 :

	Steel toecap		Polycarbonate toecap		Aluminium toecap (200 joules)
	Steel midsole		Non metallic midsole		
	A Electric resistance – Antistatic shoes.				
	CI Insulating sole against cold.				
	E Heel energy absorption.				
	FO Hydrocarbons resistance of the undermine sole.				
	HI Insulating sole against heat.				
	HRO Heat resistance of the sole.				
	M Metatarsal protection.				
	P Perforation resistance.				
	WRU Water repellent upper.				



Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) = 0,32
SRA (heel) = 0,28
SRB (flat) = 0,16
SRB (heel) = 0,13

Advantages = end users benefits

Sole : fitting adapted to the morphology of women's foot

Leather lining: for a better resistance to abrasion than textile, more comfort, softness and esthetic.

Polyurethane : antistatic, resistant to abrasion, to hydrolysis and to heat

PARABOLINE sole:

- ✓ **Excellent slip resistance** due to the profile of the sole which adapts to the nature of the ground.
- ✓ **A sole designed for women**
- ✓ **Heel shock absorber**
- ✓ **Insulating against cold.**
- ✓ **Double density polyurethane (injected)**
- ✓ **Parabolic® technology**
 - **Exceptional slip resistance** : footprint adapts itself to the nature of the ground due to the profile of the sole
 - **Spring effect** : gives a more dynamic walk
 - **Walking assistance** : the concave structure of allows a progressive deformation of the sole in order to optimize grip and facilitate walking