



OCTOPUS®DA CUT PROTECTION GLOVE LEVEL 5





Seamless knitted glove (gauge 13) with elastane in 100% high density polyethylene filament, mineral filament and 100% grey texturized polyamide thread. First 3/4 coating in blue waterproof nitrile, second coating on the palm in micro-alveolate black nitrile, elastic wrist.

THE 🚯 PRODUCT



RESISTANCE

The knitted glove with 100% high density polyethylene filament, combined with a nitrile coating, provides an excellent resistance to blade cut and to abrasion.

GRIP

The micro-alveolate coating acts like thousands of micro suction pads; this provides an exceptional grip on dry, wet and oily parts.



SEALING

The nitrile coating offers a good sealing against humidity, oils and grease

SPECIFICATIONS EN 388 Resistance to abrasion : Blade cut resistance : Tear resistance : Puncture resistance :	LEVELS • • • • • • • • •
SPECIFICATION NF EN ISO13997 Blade cut resistance :	LEVEL TDM4
SPECIFICATION EN 420 Dexterity :	LEVEL

Please contact our Sales Department :

Tel. : +33 (0)3 27 90 91 13 Fax : +33 (0)3 27 86 68 82

SAS LEBON PROTECTION INDUSTRIELLE : Z.A. La Renaissance 638 rue Léonard de Vinci – 59490 Somain – France Email : lebon@lebonprotection.com Website : www.lebonprotection.com