

34 g



**SCALE N°5**



**>> Use (\*)**

This equipment is designed for welding works, brazing and for techniques that do not require the use of a complete hood: flame cutting works, welding at low energy ...  
Welding shops, foundries, automotive industry, aeronautics...

**>> Technical features**

- ✓ Adjustable temple length.
- ✓ Single-piece lens in polycarbonate with integrated sideshield.
- ✓ Black polyamide frame.
- ✓ Attachment points on side arms for neck cord.
- ✓ Scale number 5.
- ✓ Lens thickness: 2.00 mm.
- ✓ Weight: 34 g.
- ✓ Packing: - carton of 100 units.  
- bundle of 10 units.



Learn more [www.singer.fr](http://www.singer.fr)

**>> Advantages**

- ✓ The safety combined with a dynamic and modern design.
- ✓ Easily adjustable sidearms for personalised fit and better protection.
- ✓ Reliability of an **ISO 9001** system in production.
- ✓ The mechanical resistance of polycarbonate.

**>> Conformity**

This eyewear has been tested according to the following European Standards:

- **EN 166: 2001.** Personal eye protection – Specifications – (marking: FT- Optical class 1)
- **EN 169: 2002.** Personal eye-protection. Filters for welding and related techniques.  
Transmittance requirements and recommended use (Scale number 5).
- **EN 171: 2002.** Personal eye-protection. Infrared filters. Transmittance requirements and recommended use (IR 5).
- **EN 175: 1997.** Personal protection. Equipment for eye and face protection during welding and allied processes.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**  
EU type examination certificate (**module B**) issued by **BSI** (Netherlands). Notified body **n°2797**.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Mechanical protection <b>(EN175)</b>	Symbole <b>F</b>	Impact resistant against high speed particles (corresponds to the impact of a steel ball with a diameter of 6 mm and a minimum mass of 0.86 g launched at 45 m/s).
Optical quality <b>(EN166)</b>	Symbole <b>1</b>	Class 1 continuous works (better quality).
Scale number <b>(EN169)</b>	Symbole <b>5</b>	Protection class (scale) n° 5. (filters for welding and related techniques).
Scale number <b>(EN171)</b>	Symbole <b>4-5</b>	IR 5 (infrared filters)

Your distributor **SINGER® SAFETY**

