



Special cold

Double-layer
concept

Type of use

Thanks to its technical characteristics, this glove is particularly suitable for all major works requiring dexterity in cold environment.

Refrigerating warehousing and storage, construction, public works, driver, transportation, cargo handling, maintenance of green areas, fishing, sports, ski resorts...(*)

Technical features

- ✓ **Construction:** Seamless knitter liner.
Liner with double-layer concept:
 - inner layer in warm brushed layer.
 - outer layer in polyamide.
- Elasticated knitted wrist.
- ✓ **Coating:** HPT coated palm. Uncoated back (ventilated).
- ✓ **Colour:** black.
- ✓ **Gauge:** 15.
- ✓ **Sizes:** 7, 8, 9, 10, 11, 12.
- ✓ **Packing:** - carton of 50 pairs.
- bundle of 5 pairs.



Learn more: www.singer.fr

Advantages

- ✓ Seamless knitted construction improves user comfort (no roughness, heating points) and reduce hand fatigue.
- ✓ Improves dexterity for easy handling.
- ✓ Polyamide fibres: the polyamide fibre offers high toughness, it provides good resistance against abrasion; it is resistant against mold and fungus. It is low water absorbent.
- ✓ Unique coating formulation remains soft and flexible in temperature as low as -50°C, treated with Actifresh® to kill bacteria and promote freshness.
- ✓ Elasticated knitted wrist for warm and snug fit and easy donning for maximum comfort.
- ✓ HPT coating (Hydropellent Technology). This process creates a spongy, soft, durable, flexible coating that repels liquids to provide a firm wet or dry grip.
- ✓ Encapsulated air molecules provide an inherent vibration absorption feature.


Protection
against
cold


Conformity

This glove has been tested according to the european standards: **EN388: 2003**, against mechanical risks and **EN511: 2006**, cold risks. It complies with **European Directive 89/686/CEE** on Personal Protective Equipment (PPE). (intermediate design).

EC type examination certificate issued by **SGS**, notified body n°0120.

CE

EN388: 2003. Mechanical data. Information on levels	Level 1	Level 2	Level 3	Level 4	Level 5	N100 Levels obtained	EN388: 2003
Abrasion resistance (number of cycles)	100	500	2000	8000	-	3	 3 2 3 2
Blade cut resistance (indice)	1,2	2,5	5,0	10,0	20,0	2	
Tear resistance (in newtons)	10	25	50	75	-	3	
Puncture resistance (in newtons)	20	60	100	150	-	2	

EN511: 2006
 0 2 X Convective cold: level 0 Contact cold: level 2 Water proofness: level X

Your distributor **SINGER® SAFETY**

SINGER®
safety