

Stretch nylon



**>> Type of use (\*)**

Thanks to its technical characteristics, this glove is particularly suitable for all light handling in dry conditions. Automotive assembly, warehouse & package, shipping & receiving, electronics industry, assembly stations, handling boxes, quality controls...

**>> Technical features**

- ✓ **Construction:** seamless knitted pattern. Elastic knitted wrist. Dotted palm.
- ✓ **Liner:** stretch nylon.
- ✓ **Gauge:** 13
- ✓ **Coating:** P.V.C dots on palm.
- ✓ **Colour:** white liner / blue dots.
- ✓ **Sizes:** 8, 9, 10.
- ✓ **Packing:** - carton of 100 pairs.  
- bundle of 10 pairs.



Learn more: [www.singer.fr](http://www.singer.fr)



**>> Advantages**

- ✓ Outstanding fit, flexibility and feel.
- ✓ The soft seamless liner provides exceptionnal comfort, reduces hand fatigue and will not irritate hand-even during long periods of wear.
- ✓ Elasticated knitted wrist for a snug fit.
- ✓ The back of the glove uncoated allowing the hand to breathe.
- ✓ P.V.C dotted palm: excellent grip in dry conditions for safe and secure handling of small parts and tools or fine handling tasks.
- ✓ **ISO 9001** certification for a regular and good quality of products.

**>> Conformity**

This glove has been tested according to the following European standards :


- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.

It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.** EU type examination certificate (module B) issued by **SATRA (Ireland)**. Notified body n°2777.

Download the EC declaration of conformity on: <http://docs.singer.fr>



EN 388: 2016. Protective gloves against mechanical risks							
Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	
Abrasion resistance (number of cycles)	100	500	2000	8000	-	<b>2</b>	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	<b>1</b>	
Tear resistance (in Newtons)	10	25	50	75	-	<b>4</b>	
Perforation resistance (in Newtons)	20	60	100	150	-	<b>1</b>	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	«X» means that the glove has not been submitted to the test.	2	5	10	15	22	30



Your distributor **SINGER® SAFETY**



(\*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue LS 2019\_03\_26. Copyright: Singer