

## Technical Data Sheet



### 1100 Safety Helmet

General purpose safety helmet with a 6 point plastic cradle.

1100 Safety Helmet

Specification

Colours:	White, Green, Blue, Orange, Yellow, Red
Peak:	Full or Reduced Peak
Size:	51 - 63 cm
Options:	Chinstrap, side ventilation, Corporate badging
Accessories:	Compatible with Connect range of face and hearing accessories
Weight:	375g
Corporate Badging sizes:	Front: 50 x 40mm or 45 x 45mm Back and Sides: 100 x 30mm
Packaging:	20 per colour, box size 58.5 x 44.5 x 43.5cm, box weight 9.2kg
Code:	S01(Standard), S01F (Vented), S24 (Reduced Peak), S24F (Reduced Peak Vented)

Materials

Shell:	HDPE - High Density Polyethylene
Cradle:	6 Point Plastic
Headband:	LDPE - Low Density Polyethylene
Sweatband:	None fitted



Standard &amp; Options

Standard - EN 397:1995

Options within EN 397:	MM (Molten Metal) 440V a.c. (Electrical resistance) -10°C (Low temperature performance) LD (Lateral Deformation)  Note: Electrical Resistance and Molten Metal applicable to unvented shells only
------------------------	--

Storage / Lifetime

#### Storage:

- Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)
- May be stored in the dark for up to **5 years**
- Do not store in direct/high heat or sunlight as this may distort the shell

#### Lifetime:

- The Centurion helmet has an in-use life of up to **5 years**
- Excessive wear and tear can considerably reduce the lifespan of the product

Cleaning

- Clean using warm soapy water and soft cloth
- **Do not** use solvents or abrasives