

Technical Data Sheet

Vulcan High Temperature Safety Helmet

The Vulcan fibreglass safety helmet is designed for use in industries where there is a risk from high levels of radiant heat.



Colours:	White, Yellow
Peak:	Standard
Size:	51 - 63 cm, 52 - 63cm with Ratchet
Options:	Chinstrap (S30V)
Accessories:	Compatible with Connect (S570 clips) range of face and hearing accessories
Weight:	375g
Corporate Badging:	Front: 50 x 40mm or 45 x 45mm, Back and Sides: 100 x 30mm
Helmet Accessories Clip:	Use Connect accessories clips (S570) supplied with Carriers and Ear Defenders
Packaging:	Standard: 20 per colour, box size 58.5 x 44.5 x 43.5cm, box weight 9 kg Ratchet: 10 per colour, box size 48 x 30.5 x 56cm, box weight 5kg
Code:	S22 (Standard) S22R (with Ratchet)

Shell:	GRP (Glass Reinforced Plastic)
Cradle:	6 Point Terylene webbing
Headband:	LDPE - Low Density Polyethylene
Sweatband:	Brushed Nylon with 2mm foam



EN 397:1995

Options within EN 397:	440V a.c (Electrical Resistance) -30°C (Low Temperature Performance) LD (Lateral Deformation) MM (Molten Metal)
------------------------	--

GOST 12.4.207-99 (Russian Standard):

Options within GOST:	2000V a.c (Electrical Resistance) -30°C (Low Temperature Performance) +90°C (High Temperature Performance) LD (Lateral Deformation)
----------------------	--

Storage:

- Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)
- May be stored in the dark for up to **5 years**
- Do not store in direct/high heat or sunlight as this may distort the shell

Lifetime:

- The Centurion helmet has an in-use life to up to **5 years**
- Excessive wear and tear can considerably reduce the lifespan of the product

- Clean using warm soapy water and soft cloth
- **Do not** use solvents or abrasives