



## TECHNICAL DATA SHEET

### DESCRIPTION

100% seamless grey Dyneema gloves,  
coated with grey polyurethane on palm and fingers.  
Elastic cuff, standard length from 220 mm to 260 mm.

### SIZE

6 to 10.

### USE

Synthetic gloves offer delicate and precision handling for job in relation to strong protection with cutting and abrasive material or metal plates. High dexterity, good grip.

### LIMITS OF USE

Can be used only for mechanical risks. Non waterproof gloves.  
Don't use against heat or chemical risks.

### CE CERTIFICATE

Gloves certified according EN 420-2003 and EN 388-2003.  
Protection levels: (highest level refers to the highest protection)



EN 388-2003

Abrasion resistance: level 4  
Tearing resistance: level 3  
Pulling resistance: level 4  
Puncture resistance: level 2



Dexterity: level 5

CE certificate N°2495 (issue 4) delivered by SATRA laboratories (N°0321).



**GLOVES**  
**398.013**

### MAINTENANCE - WAREHOUSING

No maintenance required. Keeping into its original packing far from humidity and light.  
To be kept under standard temperature.

### GROUPE RG

38, route de Saint-Symphorien-d'Ozon 69801 ST-PRIEST  
Tél : 04 72 73 24 24 . Fax : 04 37 25 00 03

FP398013\_eng  
AL - Novembre 2009