

PARIS 3 S3 SRC



Item code: 536002

DESCRIPTION

- Moccasin-type low safety shoes (composite and non-magnetic).
- Washable microstep microfibre upper.
- Lined and padded ankle collar.
- Fastening with a water-resistant elastic band.
- Breathable honeycomb-type mesh lining.
- Ventilated and ergonomic insole.
- Lightweight and large safety 200-joule toe cap (athermal and non-magnetic).
- Flexible. Lightweight and composite anti-perforation sole (athermal and non-magnetic).
- Flexible and light mono density PU sole.

SHOE SIZE

• 35 to 47

USE

• Multi-use lightweight and flexible moccasin-shaped safety shoe (not to be used at high temperatures).

WEIGHT

• Shoe size 42: 1.030g

MAINTENANCE / STORAGE

- Clean and brush regularly.
- Store in a cardboard box in a dry location at a normal temperature.

EC DECLARATION OF CONFORMITY

- Certified under reference 536002 PARIS S3 according to ISO standard EN 20345: 2007.
- Results:

| S3 | Backfoot area enclosed - antistatic | | |
|----|--|--|--|
| | properties. Shock absorption in the heel. | | |
| | I | | |
| | Resistance to water penetration and water | | |

- absorption. Cleated sole.
- Protective midsole against perforation up to 1.100 N.
- SRC Slip-resistant sole.
- EC certificate (No. 0161/17309/10) granted on the 10th of October 2010 by the CIMAC laboratory (0465).

Résistance au glissement SRC selon tests EN13287 et norme EN ISO 20345:2004/A1:2007

| SRA Céramique + détergent | | SRB Acier + glycérine | | | |
|------------------------------------|---|-----------------------------------|---|-----|--|
| Mini standard when flat \ge 0,32 | Min standard at the heel at 7° ≥ 0,28 | Min standard when flat $\ge 0,18$ | Min standard at the heel at 7° ≥ 0,13 | SRC | |
| 0.45 | 0.35 | 0.23 | 0.17 | SRC | |

