

JALSCREEN SAS JDR20

S3 SRC

EN ISO 20345:2011

38 to 47

- Full grain leather
- J-Smarter PU single-density sole



- ❖ Black safety shoe, derby type. Straight toe-cap.
- ❖ Classic and elegant design.
- ❖ Water-repellent full-grain leather upper, 1,5/ 1,7 mm thick.
- ❖ Leather lining quarter.
- ❖ Lined full grain leather tongue.
- ❖ Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- ❖ Fastens with black laces : 75 cm.
- ❖ **J-confort**, anatomic footbed in soft micro-channelled material, lined with breathable and abrasion-resistant Vita- Plus fabric.. Antistatic.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Stab-resistant **FleXtane™** insole and liner by Jallatte, antistatic, 100 % composite. Sewn directly onto the upper and covering 100 % of the foot for total protection.
- ❖ 200 Joules steel toe-cap

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,34** (>0,32) – On the heel **0,29** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,19** (>0,18) – On the heel: **0,15** (>0,13)

Single density polyuréthane sole :

- Highly resistant to oils and hydrocarbons
- The pattern design is purposed made to enhance comfort while waling and standing.
- Abrasion resistant.
- Heel-shock absorption > 20 Joules.



Weight	Gross weight (42): 1218 g / Net weight (42): 1000 g		
Size	38 au 39	40 au 45	46 au 47
Packaging	5 pairs	10 pairs	5 pairs
Dimensions	685 x 225 x 345	685 x 440 x 345	685 x 225 x 345