

TOBAGO S1 P SRC



- FT 544100 - UPDATE 07-2021

Item code : **544100**

DESCRIPTION

- Low safety shoe ventilated.
- Suede leather upper with breathable ventilation.
- Padded collar
- With padded leather tongue. Lacing system with eyelets.
- Breathable honeycomb type mesh lining.
- Ventilated and ergonomic insole.
- Lightweight 200 joules aluminium toe cap.
- Flexible, lightweight and composite anti-perforation sole (athermal and non-magnetic).
- PU2D sole assembly.

EU DECLARATION OF CONFORMITY

- Certified according to standard EN ISO 20345:2011.
- Results:
 - S1P** Antistatic properties
Outer sole with studs
Energy absorption in the heel area
Anti-perforation midsole up to 1100N
 - SRC** Slip resistance
- EU Certificate N° F-155-01316-18 issued on 9th november, 2018 by the notified body CIMAC (N° 0465).

SIZE

- 35 to 47

USE

- Multi-use low safety shoes (except fluid projection).

WEIGHT

- Shoe size 42 : 970g

MAINTENANCE / STORAGE

- Clean, brush and polish regularly
- Store in a cardboard box in a dry location to normal temperature

SRC Slip resistance tests results - EN Standard EN ISO 20345:2011				
SRA Ceramic + détergent		SRB Steel + glycerine		SRC
mini std on flat ≥ 0,32	mini std on heel ≥ 0,28	mini std on flat ≥ 0,18	mini std on heel ≥ 0,13	
0.33	0.30	0.19	0.14	SRC