



# DALLAS S1P SRC



FT544102 - Mise à Jour MCADR 06-2021

Item Code: 544102

### DESCRIPTION

- Low safety shoes sneaker style.
- Suede leather upper and canvas fabric.
- Lined and padded ankle collar.
- Padded bellows tongue fastening system. Lacing closed eyelets.
- Breathable honeycomb-type mesh lining.
- Ventilated ergonomic insole.
- Lightweight and large safety 200 Joules aluminium toe cap.
- Flexible, lightweight and composite anti-perforation sole (athermal and amagnetic).
- PU2D sole assembly.

### EU DECLARATION OF CONFORMITY

- Certified under 544102 DALLAS S1P SRC according to standard EN ISO 20345 : 2011.
- Results :
  - S1P Backfoot area enclosed- antistatic properties. Shock absorption in the heel. Cleated sole. Protective midsole against perforation up to 1100N.
  - SRC Slip-resistant sole.
- EU certificate N° F-155-01768-19 of the 8th of March 2019 by the CIMAC notified body laboratory (0465).

### SHOE SIZE

35 to 47

### USE

- Multi-use safety low shoes sport style (except fluid projections).

### WEIGHT

- Shoe size 42 : 1020g

### MAINTENANCE/ STORAGE

- Clean and brush regularly.
- Store in a cardboard box in a dry location at a normal temperature.

| Résistance au glissement SRC selon tests EN13287 et norme EN ISO 20345:2011 |                                 |                             |                                 |     |
|-----------------------------------------------------------------------------|---------------------------------|-----------------------------|---------------------------------|-----|
| SRA<br>Céramique + détergent                                                |                                 | SRB<br>Acier + glycérine    |                                 | SRC |
| mini norme à plat<br>≥ 0,32                                                 | mini norme au talon à 7° ≥ 0,28 | mini norme à plat<br>≥ 0,18 | mini norme au talon à 7° ≥ 0,13 |     |
| 0.52                                                                        | 0.48                            | 0.23                        | 0.18                            | SRC |

