

ALPEN 53 HI HRO SRC _____



Code: 544121G

DESCRIPTION

- · Ankle safety boots (composite).
- Water-resistant oiled grain leather upper.
- Ankle protection with lined and padded ankle collar.
- Padded bellows tongue fastening system. Lacing with closed ٠ metal loops.
- Breathable honeycomb-type mesh lining.
- Ventilated and ergonomic insole. • Lightweight and large safety 200-joule toe cap (athermal and •
- non-magnetic). Flexible, lightweight and composite anti-perforation sole ٠ (athermal and non-magnetic).
- · Vibram® PU/Nitrile sole assembly with an overcap part.

SHOE SIZE

38 to 48

Size	chart	·

38 39 40 41 42 43 44 45 46 47 48

USE

· Multi-use safety ankle boots whose sole can withstand contact heat.

WEIGHT

• Shoe size 42: 1.440g

MAINTENANCE / STORAGE

- · Clean, brush and polish or grease regularly.
- Store in a cardboard box in a dry location at a normal temperature.

EC DECLARATION OF CONFORMITY

- Certified under reference 544121G ALPEN according to ISO standard EN 20345: 2011.
- · Results:

uits.	
S3	Backfoot area enclosed - antistatic properties.
	Shock absorption in the heel.
	Resistance to water penetration and water absorption.
	Cleated sole.
	Protective midsole against perforation up
	to 1.100 N.
HI	Heat insulation
HRO	Sole which can withstand a contact heat
	of 300°C during 60 seconds.
SRC	Slip-resistant sole.

• EC certificate (No. 359160301/OF) of the 20th of January 2016 granted by the RICÓTEST laboratory (0498)

SLIP RESISTANCE SRC according EN13287 tests and standard EN ISO 20345:2011

SRA		SRB			
	Ceramic + Sodium lauryl sulfate		Steel + glycerin		
	Mini standard when flat $\ge 0,32$	Min standard at the heel at 7° ≥ 0,28	Min standard when flat ≥ 0,18	Min standard at the heel at 7° ≥ 0,13	SRC
	0.39	0.29	0.21	0.14	SRC

