

MONTANA 3 S3 HI HRO SRC



Quick fastening system



VIBRAM® sole

Item code: **544123G**

544123G - Update ID 03-2018

DESCRIPTION

- Composite and non-magnetic safety leather ranger boots.
- Pull-up water-resistant full grain leather upper with a Stark reinforcement on the forefoot and at the rear.
- Ankle protection with a lined and padded ankle collar.
- Padded leather bellows tongue fastening system. Lacing with non-magnetic octagonal eyelets and fine hooks on the top.
- Breathable honeycomb-type mesh lining.
- Ventilated and ergonomic insole.
- Lightweight and large safety 200-joule toe cap (athermal and non-magnetic).
- Flexible, lightweight and composite anti-perforation sole (athermal and non-magnetic).
- Vibram® PU/Nitrile sole assembly with an overcap part.

SHOE SIZE

- 36 to 48

Size chart :

36	37	38	39	40	41	42	43	44	45	46	47	48
----	----	----	----	----	----	----	----	----	----	----	----	----

USE

- Multi-use all-weather safety ranger boots which are entirely non-magnetic and whose sole assembly can withstand contact heat.

WEIGHT

- Shoe size 42 : 1480 g

MAINTENANCE / STORAGE

- Clean, brush and polish or grease regularly.
- Store in a cardboard box in a dry location at a normal temperature.

EC DECLARATION OF CONFORMITY

- Certified under reference 544123G MONTANA 3 according to ISO standard EN 20345: 2011
- Results :
 - S3 Backfoot area enclosed - antistatic properties.
Shock absorption in the heel.
Resistance to water penetration and water absorption.
Cleated sole.
Protective midsole against perforation up to 1.100 N.
 - HRO Sole which can withstand a contact heat of 300°C during 60 secondes.
 - HI Insulated against the heat.
 - SRC Slip-resistant sole.
- EC certificate N°359160302/OF of the 20th of January 2016 granted by the RICOTEST (0498).

SLIP RESISTANCE SRC according EN13287 tests and standard EN ISO 20345:2011

SRA Ceramic + Sodium lauryl sulfate		SRB Steel + glycerin		SRC
Mini standard when flat $\geq 0,32$	Min standard at the heel at 7° $\geq 0,28$	Min standard when flat $\geq 0,18$	Min standard at the heel at 7° $\geq 0,13$	
0.39	0.29	0.21	0.14	SRC