

QUEBEC PRO S3 HI HRO SRC



544124G - Update MP 05-2018

Item code : 544124G

DESCRIPTION

- Safety high boot outdoor style for industry.
- One piece water-resistant full grain leather upper with a reinforcement at the back.
- Ankle protection with a lined and padded Cordura® ankle collar.
- Padded bellows tongue fastening system. Lacing eyelets.
- Breathable honeycomb-type textile lining.
- Ventilated and ergonomic insole.
- Lightweight and large safety 200 joules toe cap (athermal and non-magnetic).
- Flexible, lightweight and composite anti-perforation sole (athermal and non-magnetic).
- Vibram® PU/Nitrile sole with ubercap.

SHOE SIZE

- 36 to 48

Size chart:

| | | | | | | | | | | | | |
|----|----|----|----|----|----|----|----|----|----|----|----|----|
| 36 | 37 | 38 | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 |
|----|----|----|----|----|----|----|----|----|----|----|----|----|

USE

- Multi-use all-weather safety high boot whose sole assembly can withstand contact heat.

WEIGHT

- Size 42 : 1450 g

MAINTENANCE / STORAGE

- Clean. Brush and polish or grease regularly.
- Store in a cardboard box in a dry location at a normal temperature.

EC DECLARATION OF CONFORMITY

- Certified under reference 544124G QUEBEC PRO according to standard EN ISO 20345 : 2011.
- Results :

| | |
|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| S3 | Backfoot area enclosed - antistatic properties. Shock absorption in the heel. Resistance to water penetration and water absorption. Cleared sole. Protective midsole against perforation up to 1.100 N. |
| HRO | Sole which can withstand a contact heat of 300°C during 60 secondes. |
| HI | Insulated against the heat. |
| SRC | Slip-resistant sole. |
- EC certificate N°359154101/OF of October 9th 2015 granted by RICOTEST Laboratory (0498).

SRC slip-resistance according to EN13287 tests and standard EN ISO 20345:2011

| SRA Ceramic + detergent | | SRB Steel + glycerin | | SRC |
|----------------------------------------|---------------------------------------------------|---------------------------------------|---------------------------------------------------|-----|
| Mini standard when flat $\geq 0,32$ | Min standard at the heel at 7°C $\geq 0,28$ | Min standard when flat $\geq 0,18$ | Min standard at the heel at 7°C $\geq 0,13$ | |
| 0.40 | 0.32 | 0.20 | 0.16 | SRC |