



# MEMPHIS S3 SRC



FT 544127-UPDATEMCADR 06-2021

Code: **544127**

## DESCRIPTION

- Safety ankle boots outdoor sport style.
- Full grain leather water repellent upper with ventilations textile fabric on the sides.
- Ankle protection: lined and padded ankle collar.
- Padded bellows tongue fastenning system. Textile lace-loops.
- Breathable honeycomb-type mesh lining.
- Ventilated and ergonomic insole.
- Steel toe cap.
- Flexible, lightweight and Coposite antiperforation sole (athermal and non magnetic).
- Vibram PU/TPU sole with overcap.

## SHOE SIZE

- 38 at 47

## USE

- Multi-use safety ankle boots outdoor sport style.

## WEIGHT

- Size 42 : 1270 g

## MAINTENANCE-STORAGE

- Clean and brush regularly.
- Store into its original packaging in a dry location at normal temperature.

## EU DECLARATION OF CONFORMITY

- Certified under reference 544127 MEMPHIS S3 SRC according to the EN ISO 20345 : 2011.
- Results
  - S3 Backfoot area enclosed - Antistatic properties - Shock absorption in the heel.  
Resistance to water penetration and water absorption.  
Cleated sole.  
Protective midsole against perforation up to 1100 N.
  - SRC Slip-resistant sole.
- EU certified N° 359181702/OF of the 26th of April 2018 granted by the RICOTEST laboratory (0498)

| Résistance au glissement SRC selon tests EN13287 et norme EN ISO 20345:2011 |                                 |                             |                                 |     |
|-----------------------------------------------------------------------------|---------------------------------|-----------------------------|---------------------------------|-----|
| SRA<br>Céramique + détergent                                                |                                 | SRB<br>Acier + glycérine    |                                 | SRC |
| mini norme à plat<br>≥ 0,32                                                 | mini norme au talon à 7° ≥ 0,28 | mini norme à plat<br>≥ 0,18 | mini norme au talon à 7° ≥ 0,13 |     |
| 0.32                                                                        | 0.30                            | 0.19                        | 0.19                            | SRC |