

# ARIZONA ZIP S3 HRO HI CI WR SRC



VIBRAM® sole


Item code: **544134**

544134 - Update MP 05-2018

## DESCRIPTION

- Composite safety leather ranger boots.
- Pull-up water-resistant full grain leather upper with a SympaTex® lining
- Ankle protection with a lined and padded ankle collar.
- Padded leather bellows tongue fastening system. Lacing with hooks and zip system.
- Breathable honeycomb-type mesh lining.
- Ventilated and ergonomic insole.
- Lightweight and large safety 200-joule toe cap (athermal and non-magnetic).
- Flexible, lightweight and composite anti-perforation sole (athermal and non-magnetic).
- Vibram® PU/Nitrile sole assembly with an overcap part.

## SHOE SIZE

- 36 to 48

Size chart :

36	37	38	39	40	41	42	43	44	45	46	47	48
----	----	----	----	----	----	----	----	----	----	----	----	----

## USE

- Multi-use all-weather safety ranger boots.

## WEIGHT

- Shoe size 42 : 1700 g

## MAINTENANCE / STORAGE

- Clean, brush and polish or grease regularly.
- Store in a cardboard box in a dry location at a normal temperature.

## EC DECLARATION OF CONFORMITY

- Certified under reference 544134 ARIZONA ZIP according to ISO standard EN 20345: 2011
- Results :
 

S3	Backfoot area enclosed - antistatic properties. Shock absorption in the heel. Resistance to water penetration and water absorption. Cleated sole. Protective midsole against perforation up to 1.100 N.
HRO	Sole which can withstand a contact heat of 300°C during 60 secondes.
HI	Insulated against the heat.
CI	Cold insulation
WR	Water resistant footwear
SRC	Slip-resistant sole.
- EC certificate N°359164304/OF of the 24th of october 2016 granted by the RICOTEST (0498).

SLIP RESISTANCE SRC according EN13287 tests and standard EN ISO 20345:2011				
SRA Ceramic + Sodium lauryl sulfate		SRB Steel + glycerin		SRC
Mini standard when flat $\geq 0,32$	Min standard at the heel at 7° $\geq 0,28$	Min standard when flat $\geq 0,18$	Min standard at the heel at 7° $\geq 0,13$	
0.40	0.32	0.20	0.16	SRC