

# CHICAGO S3 HRO SRC



Item code: 544204

## DESCRIPTION

- Ankle safety boots sport boxing style non-magnetic.
- Very flexible water-resistant full grain leather upper with caoutchouc reinforcement in front of.
- Ankle protection with lined and padded ankle collar.
- Padded bellows tongue fastening system. Lacing with eyelets
- Breathable honeycomb-type mesh lining.
- Ventilated and ergonomic insole.
- Lightweight and large safety 200-joule toe cap (athermal and • non-magnetic).
- Flexible, lightweight and composite anti-perforation sole (athermal and non-magnetic).
- Flexible EVA /Nitrile sole assembly with an overcap part.

## SHOE SIZE

38 to 47 Size chart ·

38	39	40	41	42	43	44	45	46	47

## USE

· Multi-use safety ankle boots whose sole can withstand contact heat.

#### WEIGHT

• Shoe size 42: 1.120g

## **MAINTENANCE / STORAGE**

- · Clean, brush and polish or grease regularly.
- Store in a cardboard box in a dry location at a normal temperature.

## EC DECLARATION OF CONFORMITY

٠	Certified under reference 544204 CHICAGO according
	to the FN ISO 20345:2011 standard.

Results:

ults:	
S3	Backfoot area enclosed - antistatic properties.
	Shock absorption in the heel.
	Resistance to water penetration and water
	absorption.
	Cleated sole.
	Protective midsole against perforation up
	to 1.100 N.
HI	Heat insulation
HRO	Sole which can withstand a contact heat
	of 300°C during 60 seconds.
SRC	Slip-resistant sole.
	(N) = 0.000 (40.000 (40)) = 5.4 = 0.00 = 5.00 = 5.00 = 10.000 = 10.000 = 10.000 = 10.000 = 10.000 = 10.000 = 10.000 = 10.000 = 10.000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.0000 = 10.00000 = 10.00000 = 10.00000 = 10.00000 = 10.00000 = 10.00000 = 10.00000 = 10.00000 = 10.00000 = 10.00000 = 10.00000 = 10.00000 = 10.00000 = 10.000000 = 10.000000 = 10.0000000000

EC certificate (No. 0161/19460/12) of the 26<sup>th</sup> of October 2012 granted by the CIMAC laboratory (0465)

SLIP RESISTANCE SRC according EN13287 tests and standard EN ISO 20345:2011

5	SRA	S				
Ceramic + Soc	dium lauryl sulfate	Steel +				
Mini standard when flat ≥ 0,32	Min standard at the heel at 7° ≥ 0,28	Min standard when flat ≥ 0,18	Min standard at the heel at 7° ≥ 0,13	SRC		
0.43	0.38	0.18	0.13	SRC		

