


APOLLON 2 ESD S3S CI SR FO

SAFETY SHOES


544223


BENEFITS

DESCRIPTION

- High ESD safety shoes such as sneakers, R GO'Pulse range.
- R GO'Pulse sole: PU2D with BASF Infinergy® insert to cushion - stabilize - impulse.
- Very soft tumbled and supple water-repellent full-grain leather upper with textile side vents.
- 200 joule aluminum safety toe, lightweight.
- Composite anti-perforation sole (small 3mm tip), light, flexible, athermal and non-magnetic.
- Anatomical and perforated PU insole, improving weight distribution by cushioning pressure points.
- Lined quilted upper.
- Gusseted closure and quilted canvas tab. Eyelet lacing on leather reinforcement.
- One-piece seamless forefoot.
- Breathable honeycomb lining.

USE

- High ESD safety shoes type multi-purpose full-grain leather sneakers
- For all ESD environments

- Innovative R GO'PULSE = PU2D + Infinergy® insert from BASF to cushion-stabilize-impulse.
- Full-grain tumbled and supple leather upper.
- Certified model with SECOSOL orthopedic insoles.

SIZE

35 -> 48

WEIGHT

Size 42: 1.185 kg

VARIANTS

REPLACED MODEL



544222

 544217
 APOLLON S3 ESD HI CI
 SRC
 EN ISO 20345:2011

APOLLON 2 ESD S3S CI SR FO

SAFETY SHOES

update : 04/2025

STANDARDISATION

Compliance with the essential safety requirements has been verified using the following harmonised standards:

EN ISO 20345:2022

S3S

S3S: Closed back - Antistatic properties.
Energy absorption from the heel. Resistance to water penetration and water absorption.
Studded sole.
Anti-puncture midsole up to 1100 N with a small tip, 3 mm in diameter.

CI

CI: Insulation of the sole against the cold

SR

SR: Slip-resistant rubber outsole (SR)

FO

FO: Hydrocarbon resistant sole



ESD: Model suitable for ESD environments



SLIP RESISTANCE

Additional requirement SR: Ceramic floor/glycerine
Coefficient of friction/heel: 0.29 (≥ 0.19). Front: 0.25 (≥ 0.22)

PACKAGING

Pair packaged in a kraft box made from 70% recycled materials.



x1



x5 or x10

ADDITIONAL PRODUCTS



The existence of an assessed CSR approach by the manufacturer, certified by an independent body.



Obtaining a label for the product OR ISO 14001 certification for the manufacturing site.



The place of manufacture of the product located within a radius of 2000 km of France AND Country ranked in the Top 30 of the IPE 2022.



At least 15% of the product is made from recycled or bio-sourced materials.



Groupe RG

817 rue Nicéphore Niépce, 69800 Saint Priest
+32 (4) 72 23 24 30 Internet : www.groupe-rg.com