

## PEGASE 2 ESD S1PS SR FO

### SAFETY SHOES


**544224**


✓ ✓ - -

### BENEFITS

### DESCRIPTION

- ESD low-cut sport-type safety shoes, R GO'Pulse range.
- R GO'Pulse semelation = PU2D + BASF Infinergy® to cushion - stabilize - impulse.
- Very soft upper with breathable mesh ventilation.
- 200 joule aluminum safety toe, lightweight.
- Composite anti-perforation sole (small 3mm tip), light, flexible, athermal and non-magnetic.
- Anatomical and perforated PU insole, improving weight distribution by cushioning pressure points.
- Lined quilted upper.
- Gusseted closure and quilted canvas tab. Eyelet lacing on leather reinforcement.
- Breathable honeycomb lining.

### USE

- ESD safety shoes for multi-purpose sports (except for splashing fluids).
- For all ESD environments

- Innovative R GO'PULSE = PU2D + Infinergy® insert from BASF to cushion-stabilize-impulse.
- Very soft upper with breathable mesh ventilation.
- Certified model with SECOSOL orthopedic insoles.

### SIZE

35 -&gt; 48

### WEIGHT

Size 42: 1.125kg

### VARIANTS



544225

### REPLACED MODEL

 544214  
 PEGASE S1P ESD SRC  
 EN ISO 20345:2011

## PEGASE 2 ESD S1PS SR FO

### SAFETY SHOES

update : 05/2025

#### STANDARDISATION

Compliance with the essential safety requirements has been verified using the following harmonised standards:

EN ISO 20345:2022

### S1PS

S1PS: Closed back - Anti-static properties. Energy absorption. Puncture-proof midsole up to 1100 N with a small tip, 3 mm in diameter.

### SR



SR: Slip-resistant rubber outsole (SR)

### FO



FO: Hydrocarbon resistant sole



ESD: Model suitable for ESD environments



#### SLIP RESISTANCE

Additional requirement SR: Ceramic floor/glycerine  
Coefficient of friction/heel: 0.29 ( $\geq 0.19$ ). Front: 0.25 ( $\geq 0.22$ )

#### PACKAGING

Pair packaged in a kraft box made from 70% recycled materials.



x1



x5 or x10

#### ADDITIONAL PRODUCTS



The existence of an assessed CSR approach by the manufacturer, certified by an independent body.



Obtaining a label for the product OR ISO 14001 certification for the manufacturing site.



The place of manufacture of the product located within a radius of 2000 km of France AND Country ranked in the Top 30 of the IPE 2022.



At least 15% of the product is made from recycled or bio-sourced materials.

Groupe RG

817 rue Nicéphore Niépce, 69800 Saint Priest  
+32 (4) 72 23 24 30 Internet : [www.groupe-rg.com](http://www.groupe-rg.com)