

## JUPITER 2 ESD S3S CI SR FO

### SAFETY SHOES


**544227**


### BENEFITS

### DESCRIPTION

- High ESD safety shoes, R GO'Pulse range.
- R GO'PULSE Infinergy= PU2D + Infinergy® semelage from BASF to dampen-stabilize-impulse.
- Upper made of highly abrasion-resistant, breathable and water-repellent Putek® PLUS textile.
- 200 joule aluminum safety toe, lightweight.
- Composite anti-perforation sole, light, flexible, athermal and non-magnetic.
- Anatomical and perforated PU insole, improving weight distribution by cushioning pressure points.
- Seamless one-piece upper front. Full grain leather back piece.
- Quilted and lined upper upper.
- Gusseted closure and quilted canvas tab. Eyelet lacing on leather reinforcement
- Breathable honeycomb lining.

### USE

- High ESD type Tek PLUS multi-purpose PU sneaker type safety shoes.
- For all ESD environments

- Innovative R GO'PULSE = PU2D + Infinergy® insert from BASF to cushion-stabilize-impulse.
- Textile upper in Putek® PLUS.
- Certified model with SECOSOL orthopedic insoles.

### SIZE

35 -&gt; 48

### WEIGHT

Size 42: 1.085 kg

### VARIANTS

### REPLACED MODEL



544226

 544219  
 JUPITER S3 ESD SRC  
 EN ISO 20345:2011

# JUPITER 2 ESD S3S CI SR FO

## SAFETY SHOES

update : 05/2025

### STANDARDISATION

Compliance with the essential safety requirements has been verified using the following harmonised standards:

EN ISO 20345:2022

**S3S**

S3S: Closed back - Antistatic properties.  
Energy absorption from the heel. Resistance to water penetration and water absorption.  
Studded sole.  
Anti-puncture midsole up to 1100 N with a small tip, 3 mm in diameter.

**CI**

CI: Insulation of the sole against the cold

**SR**

SR: Slip-resistant rubber outsole (SR)

**FO**

FO: Hydrocarbon resistant sole



ESD: Model suitable for ESD environments



### SLIP RESISTANCE

Additional requirement SR: Ceramic floor/glycerine  
Coefficient of friction/heel: 0.29 ( $\geq 0.19$ ). Front: 0.25 ( $\geq 0.22$ )

### PACKAGING

Pair packaged in a kraft box made from 70% recycled materials.



x1



x5 or x10

### ADDITIONAL PRODUCTS



The existence of an assessed CSR approach by the manufacturer, certified by an independent body.



Obtaining a label for the product OR ISO 14001 certification for the manufacturing site.



The place of manufacture of the product located within a radius of 2000 km of France AND Country ranked in the Top 30 of the IPE 2022.



At least 15% of the product is made from recycled or bio-sourced materials.

Groupe RG

817 rue Nicéphore Niépce, 69800 Saint Priest  
+32 (4) 72 23 24 30 Internet : [www.groupe-rg.com](http://www.groupe-rg.com)