

OLYMPE 2 ESD S3S HI CI LG SC

SAFETY SHOES


544228


BENEFITS

DESCRIPTION

- Low ESD safety shoes, R GO'Pulse range.
- R GO'Pulse sole: PU2D with BASF Infinergy® insert to cushion - stabilize - impulse.
- 200 joule aluminum safety toe, lightweight.
- Composite anti-perforation sole, light, flexible, athermal and non-magnetic.
- Insulating semeling against cold, heat and resistant to hydrocarbons.
- Sole with grip system for ladder.
- Water-repellent pull-up leather upper
- Anti-abrasion Matrix reinforcement in the forefoot.
- Anatomical and perforated PU insole, improving weight distribution by cushioning pressure points.
- Gusseted closure and quilted canvas tab. Lacing with lace loops.
- Breathable honeycomb lining.

USE

- High ESD safety shoes type multi-purpose leather leather flower.
- For all ESD environments

- Innovative R GO'PULSE = PU2D + Infinergy® insert from BASF to cushion-stabilize-impulse.
- Anti-abrasion Matrix reinforcement in the forefoot.
- Sole with grip system for ladder.
- Certified model with SECOSOL orthopedic insoles.

SIZE

35 -> 48

WEIGHT

Size 42: 1.295 kg

VARIANTS



REPLACED MODEL

544210
 OLYMPE S3 ESD HI CI SRC
 EN ISO 20345:2011

OLYMPE 2 ESD S3S HI CI LG SC

SAFETY SHOES

update : 05/2025

STANDARDISATION

Compliance with the essential safety requirements has been verified using the following harmonised standards:

EN ISO 20345:2022 + A1:2024

S3S

S3S: Closed back - Antistatic properties.
 Energy absorption from the heel. Resistance to water penetration and water absorption.
 Studded sole.
 Anti-puncture midsole up to 1100 N with a small tip, 3 mm in diameter.

HI



HI: Heat insulation of the sole

CI



CI: Insulation of the sole against the cold

LG



LG: Lader Grip Ladder Grip System

SC



SC: Abrasion resistant stone guard

SR



SR: Slip-resistant rubber outsole (SR)



ESD: Model suitable for ESD environments



SLIP RESISTANCE

Additional requirement SR: Ceramic floor/glycerine
 Coefficient of friction/heel: 0.26 (≥ 0.19). Front: 0.29 (≥ 0.22)

PACKAGING

Pair packaged in a kraft box made from 70% recycled materials.



x1



x5 or x10

ADDITIONAL PRODUCTS



The existence of an assessed CSR approach by the manufacturer, certified by an independent body.



Obtaining a label for the product OR ISO 14001 certification for the manufacturing site.



The place of manufacture of the product located within a radius of 2000 km of France AND Country ranked in the Top 30 of the IPE 2022.



At least 15% of the product is made from recycled or bio-sourced materials.

Groupe RG

817 rue Nicéphore Niépce, 69800 Saint Priest
 +32 (4) 72 23 24 30 Internet : www.groupe-rg.com