

# ATHENA 2 ESD S1PS SR FO

**SAFETY SHOES** 



544230















### **DESCRIPTION**

- Low-cut ESD safety shoes such as sneakers, R GO'Pulse range.
- $\bullet$  R GO'Pulse sole: PU2D with BASF Infinergy® insert to cushion stabilize impulse.
- Very soft leather, rumpen with textile side vents.
- 200 joule aluminum safety toe, lightweight.
- Composite anti-perforation sole (small 3mm tip), light, flexible, athermal and non-magnetic.
- Anatomical and perforated PU insole, improving weight distribution by cushioning pressure points.
- Lined quilted upper.
- ullet One-piece seamless forefoot.
- Gusseted closure and quilted canvas tab. Eyelet lacing on leather reinforcement.
- Breathable honeycomb lining.

#### **USE**

- ESD safety shoes for multi-purpose sports (except for splashing fluids).
- For all ESD environments

## **BENEFITS**

- Innovative R GO'PULSE = PU2D + Infinergy® insert from BASF to cushion-stabilize-impulse.
- Full-grain tumbled and supple leather upper.
- Certified model with SECOSOL orthopedic insoles.

SIZE

WEIGHT

35 -> 42

Size 38: 0.905 kg

**VARIANTS** 

REPLACED MODEL

544212

ATHENA S1P ESD SRC EN ISO 20345:2011



# **ATHENA 2 ESD S1PS SR FO**

**SAFETY SHOES** 

date : 05/2

### **STANDARDISATION**

Compliance with the essential safety requirements has been verified using the following harmonised standards:

EN ISO 20345:2022

S<sub>1</sub>PS

S1PS: Closed back - Anti-static properties. Ener-

gy absorption. Puncture-proof midsole up to 1100 N with a small tip, 3 mm in diameter.



SR: Slip-resistant rubber outsole (SR)



FO: Hydrocarbon resistant sole



ESD: Model suitable for ESD environments



### **SLIP RESISTANCE**

Additional requirement SR: Ceramic floor/glycerine Coefficient of friction/heel: 0.29 ( $\geq$ 0.19). Front: 0.25 ( $\geq$ 0.22)

#### **PACKAGING**

Pair packaged in a kraft box made from 70% recycled materials.



x1

x5 or x10

### **ADDITIONAL PRODUCTS**





The existence of an assessed CSR approach by the manufacturer, certified by an independent body.



Obtaining a label for the product OR ISO 14001 certification for the manufacturing site.



The place of manufacture of the product located within a radius of 2000 km of France AND Country ranked in the Top 30 of the IPE 2022.



At least 15% of the product is made from recycled or bio-sourced materials.