

NEVADA S3 SRC



FT545001U - Update 07-2021

Item code: **545001U**

DESCRIPTION

- Composite an functional low safety shoes.
- Water-resistant pigmented full grain leather upper with no stitching on the outside surface of the foot and with a lateral retro-reflecting cord.- Lined and padded ankle collar.
- Padded bellows tongue fastening system. Lacing closed metal loops.
- Breathable honeycomb-type mesh lining.
- Ventilated and ergonomic insole.
- Lightweight and large safety 200-joule toe cap (athermal and non-magnetic).
- Flexible, lightweight and composite anti-perforation sole (athermal and non-magnetic).
- PU2D sole assembly with an overcap.

SHOE SIZE

- 38 to 47

USE

- Multi-use low safety shoes.

WEIGHT

- Shoe size 42 : 1150g

MAINTENANCE / STORAGE

- Clean. brush and polish.
- Store in a cardboard box in a dry location at a normal temperature.

EU DECLARATION OF CONFORMITY

- Certified under reference 545001U NEVADA according to ISO standard EN ISO 20345 : 2011.
- Results :
 - S3 Backfoot area enclosed - antistatic properties.
Shock absorption in the heel.
Resistance to water penetration and water absorption.
Cleated sole.
Protective midsole against perforation up to 1.100 N.
 - SRC Slip-resistant sole.
- EU certificate N° F-155-01226-18 of the 24th october 2018 from notified body CIMAC (0465).

Résistance au glissement SRC selon tests EN13287 et norme EN ISO 20345:2004/A1:2007				
SRA Céramique + détergent		SRB Acier + glycérine		SRC
Mini standard when flat $\geq 0,32$	Min standard at the heel at 7° $\geq 0,28$	Min standard when flat $\geq 0,18$	Min standard at the heel at 7° $\geq 0,13$	
0.41	0.31	0.21	0.18	SRC