

BOSTON 4 53 SRC



FT552010U - Update SR 03-2014

Item code: **552010U**

DESCRIPTION

- Trainer-type functional low safety shoes.
- Pull-up water-resistant nubuck grain leather upper with decorative canvas patches and lateral retro-reflecting cord.
- Lined and padded ankle collar.
- Fastening with padded fabric bellows tongue. Lacing with eyelets and closed metal loops.
- Breathable honeycomb-type mesh lining.
- Ventilated and ergonomic insole.
- Lightweight, athermal, non-magnetic and large safety 200-joule toe cap.
- Stainless steel anti-perforation sole.
- PU2D sole assembly with an overcap.

SHOE SIZE

- 38 to 47

USE

- Multi-use functional low safety shoes.

WEIGHT

- Shoe size 42 : 1180 g

MAINTENANCE / STORAGE

- Clean, brush and polish or grease regularly.
- Store in a cardboard box in a dry location at a normal temperature.

EC DECLARATION OF CONFORMITY

- Certified under reference 552010U BOSTON 4 according to ISO standard EN ISO 20345 : 2011.
- Résultats :
 - S3 Backfoot area enclosed - antistatic properties.
Shock absorption in the heel.
Resistance to water penetration and water absorption.
Cleated sole.
Protective midsole against perforation up to 1.100 N.
 - SRC Slip-resistant sole.
- EC certificate N°0161/20795/13 of the 2th décembre 2013 granted by the CIMAC laboratory (0465).

Résistance au glissement SRC selon tests EN13287 et norme EN ISO 20345:2004/A1:2007				
SRA Céramique + détergent		SRB Acier + glycérine		SRC
Mini standard when flat $\geq 0,32$	Min standard at the heel at 7° $\geq 0,28$	Min standard when flat $\geq 0,18$	Min standard at the heel at 7° $\geq 0,13$	
0.41	0.31	0.21	0.18	SRC