

ORLY 3 S3S CI FO SR

SAFETY SHOES





572312















DESCRIPTION

- Non-magnetic low shoes.
- Water-repellent full-grain leather upper.
- 200 joule composite safety toe, lightweight, athermal and non-magnetic.
- Composite anti-perforation sole, light, flexible, athermal and non-magnetic.
- Anatomical and perforated PU insole, improving weight distribution by cushioning pressure points.
- Quilted and lined upper upper.
- Closure with a large gusseted soft leather lined. Lacing with non-magnetic eyelets.
- Breathable honeycomb lining.
- PU2D sole.

USE

• Multi-purpose safety low, totally non-magnetic

BENEFITS

- Lightweight, non-magnetic design.
- Certified model with SECOSOL orthopedic insoles.

SIZE

WEIGHT

35 -> 48

Size 42: 1,197 kg

VARIANTS

REPLACED MODEL

572012 ORLY 2 S3 SRC EN ISO 20345:2011

572310



ORLY 3 S3S CI FO SR

SAFETY SHOES

STANDARDISATION

Compliance with the essential safety requirements has been verified using the following harmonised standards:

EN ISO 20345:2022 + A1:2024

S3S: Closed back - Antistatic properties. Energy absorption from the heel. Resistance to water penetration and water absorption. Studded sole. Anti-puncture midsole up to 1100 N with a small

tip, 3 mm in diameter.



CI: Insulation of the sole against the cold



FO: Hydrocarbon resistant sole



SR: Slip-resistant rubber outsole (SR)



SLIP RESISTANCE

Additional requirement SR: Ceramic floor/glycerine Coefficient of friction/heel: 0.30 (≥0.19). Front: 0.31 (≥0.22)

PACKAGING

Pair packaged in a kraft box made from 70% recycled materials.



x5 or x10

ADDITIONAL PRODUCTS





The existence of an assessed CSR approach by the manufacturer, certified by an independent body.



Obtaining a label for the product OR ISO 14001 certification for the manufacturing site.



The place of manufacture of the product located within a radius of 2000 km of France AND Country ranked in the Top 30 of the IPE 2022.



At least 15% of the product is made from recycled or bio-sourced materials.