



# LEEDS S3 SRC



• FT 5860007-UPDATEMCADR 06-2021

Code: 586007

### DESCRIPTION

- Safety low shoes composite and non magnetic sport style.
- Nubuck oiled leather water repellent upper with Stark reinforcement in front of and reflective parts on the sides.
- Ankle protection: lined and padded ankle collar.
- Padded bellows textile tongue fastening system.
- Plastics eyelets lacing on leather reinforcement.
- Breathable honeycomb-type mesh lining.
- Ventilated and ergonomic insole.
- Lightweight and large safety 200-joule composite toe cap (athermal and non magnetic).
- Flexible, lightweight and Composite antiperforation sole (athermal and non magnetic).
- PU2D sole

### SHOE SIZE

- 36 at 48

### USE

- Multi-use safety low shoes non magnetic sport style.

### WEIGHT

- Size 42 : 1190 g

### MAINTENANCE-STORAGE

- Clean and brush regularly.
- Store into its original packaging in a dry location at normal temperature.

### EU DECLARATION OF CONFORMITY.

- Certified under reference 586007 LEEDS S3 SRC according to the EN ISO 20345 : 2011.
- Results
  - S3 Backfoot area enclosed - Antistatic properties - Shock absorption in the heel.  
Resistance to water penetration and water absorption.  
Cleated sole.  
Protective midsole against perforation up to 1100 N.
  - SRC Slip-resistant sole.
- EU certified N° N° 0075/021/161/10/19/3001 EXT 01/10/19 of the 14th of October 2019 granted by the CTC laboratory (0075)

Résistance au glissement SRCselontests EN13287 et norme EN ISO 20345:2011				
SRA Céramique + détergent		SRB Acier + glycérine		SRC
mini norme à plat ≥ 0,32	mini norme au talon à 7° ≥ 0,28	mini norme à plat ≥ 0,18	mini norme au talon à 7° ≥ 0,13	
0.52	0.46	0.23	0.18	SRC



- LT system ERGOS : double antitwist system of the ankle integrated in the product to reduce the torsion of the ankle

Groupe(RG)  
bien conseillé, mieux protégé