

# MANCHESTER 2 S3 SRC



586040C - Update SR 03-2013

 Item code: **586040C**

## DESCRIPTION

- Trainer-type leather low safety shoes.
- Pull-up and oiled water-resistant full grain leather upper.
- Lined and padded ankle collar.
- Padded leather tongue fastening. Lacing with eyelets.
- Breathable mesh-type lining.
- Ventilated and ergonomic insole.
- Lightweight and large safety 200-joule toe cap (athermal and non-magnetic).
- Stainless steel anti-perforation sole.
- PU2D sole assembly.

## SHOE SIZE

- 38 to 47 (shoe sizes in 35 and 37 are possible)

## USE

- Multi-use low safety shoe.

## WEIGHT

- Pointure 42 : 1270g

## MAINTENANCE / STORAGE

- Clean. brush and polish or grease regularly.
- Store in a cardboard box in a dry location at a normal temperature.

## EC DECLARATION OF CONFORMITY

- Certified under reference 586040C MANCHESTER 2 according to ISO standard EN 20345 : 2011
- Résultats :
  - S3 Backfoot area enclosed - antistatic properties.  
Shock absorption in the heel.  
Resistance to water penetration and water absorption.  
Cleated sole.  
Protective midsole against perforation up to 1.100 N.
  - SRC Slip-resistant sole.
- EC certificate (No. 0161/17366/10) Rev.1 of the 19th of November 2013 granted by the CIMAC laboratory (0465)

| Résistance au glissement SRC selon tests EN13287 et norme EN ISO 20345:2004/A1:2007 |  |                                    |  |     |
|---|--|------------------------------------|--|-----|
| SRA<br>Céramique + détergent  |  | SRB<br>Acier + glycérine           |  | SRC |
| Mini standard when flat $\geq 0,32$   | Min standard at the heel at 7° $\geq 0,28$ | Min standard when flat $\geq 0,18$ | Min standard at the heel at 7° $\geq 0,13$ |     |
| 0.36  | 0.29                                       | 0.19                               | 0.15                                       | SRC |