



MANCHESTER N2 S3 SRC



Item code: 586041C

DESCRIPTION

- Composite leather safety low shoes (non-magnetic).
- Water-resistant full grain leather upper with Stark protection added
- Ankle protection: lined and padded ankle collar.
- Large lined flexible tongue Tongue bellows fastening system. Lacing with non-magnetic eyelets.
- Breathable honeycomb-type mesh lining.
- Ventilated and ergonomic insole.
- Lightweight and large safety 200-joule toe cap (athermal and non-magnetic).
- Flexible, lightweight and composite anti perforation sole (athermal and non-magnetic).
- PU2D sole assembly.

EU DECLARATION OF CONFORMITY

- Certified under reference 586041C MANCHESTER N2 according to the EN ISO 20345: 2011 standard.
- Results:

| | |
|------|---|
| S3 | Backfoot area enclosed - antistatic properties. Shock absorption in the heel. Resistance to water penetration and water absorption. Cleated sole. Protective midsole against perforation up to 1.100 N. |
| SRCA | Slip-resistant sole. |
- EU certificate F-155-01772-19 of the 7th of March 2019 granted by the CIMAC laboratory (0465)

SHOE SIZE

- 35 to 47

Size chart :

| | | | | | | | | | | | | |
|----|----|----|----|----|----|----|----|----|----|----|----|----|
| 35 | 36 | 37 | 38 | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 |
|----|----|----|----|----|----|----|----|----|----|----|----|----|

USE

- Entirely non-magnetic multi-use safety low shoes.

WEIGHT

- Shoe size 42: 1280 g

MAINTENANCE / STORAGE

- Clean. Brush and polish or grease regularly.
- Store in a cardboard box in a dry location at a normal temperature.

Résistance au glissement SRC selon tests EN13287 et norme EN ISO 20345:2004/A1:2007

| SRA Céramique + détergent | | SRB Acier + glycérine | | SRC |
|--|---|---------------------------------------|---|-----|
| Mini standard when flat $\geq 0,32$ | Min standard at the heel at 7° $\geq 0,28$ | Min standard when flat $\geq 0,18$ | Min standard at the heel at 7° $\geq 0,13$ | |
| 0.36 | 0.29 | 0.19 | 0.15 | SRC |

