



BARI S3 ESD SRC



FT 586066-UPDATEN/CADR 06-2021

Code: 586066

DESCRIPTION

- Full grain leather safety low ESD shoes .
- Full grain leather water repellent upper.
- Ankle protection: lined and padded ankle collar in full grain leather.
- Full grain leather padded bellows tongue .
- Lacing with speedlace system.
- Breathable honeycomb-type mesh lining.
- Ventilated and ergonomic insole.
- Lightweight and large safety 200-joule aluminium toe cap.
- Flexible, lightweight and Composite antiperforation sole (athermal and non magnetic).
- PU2D sole with high antislip design.

SHOE SIZE

- 35 at 48

USE

- Multi-use safety low ESD shoes.
- For all ESD atmospheres.

WEIGHT

- Size 42 : 1100 g

MAINTENANCE-STORAGE

- Clean and brush regularly.
- Store into its original packaging in a dry location at normal temperature.

EU DECLARATION OF CONFORMITY.

- Certified under reference 586066 BARI S3 ESD SRC according to the EN ISO 20345 : 2011.
- Results
 - S3 Backfoot area enclosed - Antistatic properties - Shock absorption in the heel.
Resistance to water penetration and water absorption.
Cleated sole.
Protective midsole against perforation up to 1100 N.
 - SRC Slip-resistant sole.
- EU certified N°0075/021/161/02/20/0445 EXT 01/02/20 of the 28th of February 2020 granted by the CTC laboratory (0075)
- ESD related to the standard CEI EN 61340-5-1: 2016

Résistance au glissement SRC selon tests EN13287 et norme EN ISO 20345:2011

SRA Céramique + détergent		SRB Acier + glycérine		SRC
mini norme à plat ≥ 0,32	mini norme au talon à 7° ≥ 0,28	mini norme à plat ≥ 0,18	mini norme au talon à 7° ≥ 0,13	
0.54	0.52	0.29	0.23	SRC



- LT system ERGOS : double antitwist system of the ankle integrated in the product to reduce the torsion of the ankle

Groupe(RG)
bien conseillé, mieux protégé