



MIAMI S1P SRC



FT586068 - Mise à Jour MCADR 11-2020

Code: 586068

DESCRIPTION

- Amagnetic low safety shoes sport style.
- Suede leather upper with ventilated textile, stark reinforcement and retro-reflecting cord on side.
- Linned and padded ankle collar.
- Padded bellows tongue fastening system. Lacing closed amagnetic loops.
- Breathable lining
- Ventilated ergonomic insole.
- Lightweight and large safety 200 Joules toe cap (athermal and amagnetic).
- Flexible, lightweight and composite anti-perforation sole (athermal and amagnetic).
- PU2D sole assembly with an overcap.

EU DECLARATION OF CONFORMITY

- Certified under 586068 MIAMI S1P SRC according to standard EN ISO 20345 : 2011.
- Results :
 - S1P Backfoot area enclosed- antistatic properties. Shock absorption in the heel. Cleated sole.
 - SRC Protective midsole against perforation up to 1100N. Slip-resistant sole.
- EU certificate N°0075/021/161/10/19/3001 EXT 03/10/19 of the 14th of October 2019 by the CTC notified body laboratory (0075).

SHOE SIZE

36 to 47

USE

- Multi use safety low shoes (except fluid projections)

WEIGHT

- Shoe size 42 : 1200g

MAINTENANCE/ STORAGE

- Clean and brush regularly.
- Store in a carboard box in a dry location at a normal temperature.

Résistance au glissement SRC selon tests EN13287 et norme EN ISO 20345:2011				
SRA Céramique + détergent		SRB Acier + glycérine		SRC
mini norme à plat ≥ 0,32	mini norme au talon à 7° ≥ 0,28	mini norme à plat ≥ 0,18	mini norme au talon à 7° ≥ 0,13	
0.52	0.48	0.23	0.18	SRC

