


Name	PB 21	
Standard	EN ISO 20345:2011 S3 HRO HI CI SRC	
Description	Black Ankle Length Welders Boot	
Weight	900 grams	
Colour	Black	

Sizes	5	6	7	8	9	10	11	12	13				
-------	---	---	---	---	---	----	----	----	----	--	--	--	--

Properties	<p>Upper – Full Grain Barton Print Buffalo Leather with higher chrome content. (Leather 1.8-2.0mm)</p> <p>Inner Lining – Moisture Wicking Textile to Vamp only.</p> <p>Toe Cap – Steel Toe Cap Resistant to 200J.</p> <p>Midsole – Stainless Steel Protective Midsole – Min. 1100N.</p> <p>Sole Unit – Dual Density Rubber/Rubber Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 300°C and SRC rated Slip Resistance.</p> <p>Footbed – Moisture Wicking, Breathable, and Washable Footbed.</p> <p>Additional Features – Kevlar Flame Resistant Stitching.</p>
------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Areas of Application	The PB 21 is suitable for use in welding environments where there is a high risk of it coming into contact with hot sparks. Made using only full grain leather and Kevlar stitching, this product is highly flame resistant and can be used for a variety of welding applications.
----------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Standard	EN ISO 20345:2011  Cat. 2	S3 HRO HI CI SRC		
----------	-----------------------------------------------------------------------------------------------------------------------	------------------------	--	--

Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.
-------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Symbols	
---------	--

Contact	Performance Brands Ltd 1200 Century Way, Thorpe Park Business Park, Colton, Leeds sales@performance-brands.co.uk www.performance-brands.co.uk
---------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------