



ddr
TECHNOLOGY

DESCRIPTION:

- Tough full grain leather with leather-lined padded collar and anti-scuff, heat-resistant rubber outer toe cap.
- Wide bellows tongue, leather-lined and padded, eyelets.
- Breathable textile lining.
- Anatomically contoured, shock absorbing washable footbed.
- Steel toe cap to 200 joules
- Stainless steel midsole for puncture resistance to 1100 Newtons.
- Dual density injected nitrile rubber non-slip sole , heat, oil and petrol and acid-resistant.
- Sizes: 38 to 49

STANDARDS:

Conforms to EN ISO20345:2011 / S3 HRO HI CI SRC

according to EC type examination certificate no. LEC FI00360361 issued by the INTERTEK laboratory on 16 November 2015.

Slip-resistant to SRC standard, tested according to EN13287 and EN ISO 20345:2004A1:2007				
SRA Ceramic + detergent		SRB Steel + glycerol		SRC
min. standard flat $\geq 0,32$	min. standard $7^\circ \geq 0,28$	min. standard flat $\geq 0,18$	min. standard $7^\circ \geq 0,13$	
0.38	0.35	0.18	0.13	

WEIGHT:

Size 42: 1700g

FT586225 - Updated AB 12-2015