

## **TECHNICAL DATASHEET**

**REFERENCE** :

E2254-100

Old référence :



The materials of this article do not contain any substance that can harm the health of the user

This PPE is in conformity with the requirements of the Directive 89/686/CEE. has been the subject of the03312149CENTEXBEL The CE marking on these items means the respect for the essentials requirements of European Directive on PPE based on the standard EN 340



A1 classe 2 / Classe 1 (Back in Proban)

ISO 11611

Class 1: Resistance to splashing of 15 drops Heat transfer time 20Kw/m²>12 s

Class2: Resistance to splashing of 25 drops Heat transfer time 20Kw/m<sup>2</sup> >16s

## Use only within the risks covered above

Maintenance:
--------------

A dirty clothe may cause a reduced protection/

no washing recommended, but dry cleaning with mineral spirits by a professional is possible

Storage : Protected from the light and in a dry place, free of moisture, oils, greases...

## Recommandation :

to wear on fire resistant clothing and to complete with appropriate PPE (pants, gloves, gaiters, face guard, welding hood ...)

в	Coat/Apron			
	Lenght	Α	Sizes	B et C
	120 cm	164-170 cm	S – T2	92-96 cm
1 70-	130 cm	170-182 cm	M – T3	96-104 cm
	140 cm	182-188 cm	L – T4	104-112 cm
	150 cm	188-194 cm	XL – T5	112-120 cm
Щ	160 cm	194-200 cm	XXL – T6	120-128 cm

For coveralls, take the greatest size between **B** or **C**. The measures must be taken on the person wearing his work clothes, because this equipment is worn over. In doubt between two sizes choose the larger one.