



+ [View More](#)

PRODUCT NUMBER: 2132545

FLEXIDYN

Handling sharp parts in a dry or greasy environment.

Overview

Reference Number  
2132545

Product Type  
Gloves

Range  
Cut and Puncture Protection

Line  
Cut resistant

Brand  
Sperian

Brand formerly known as  
PERFECT FIT

Industry

- Automotive and Part Manufacturer
- Aviation
- Building and Construction
- Catering
- Energy or Electricity
- Glass Industries
- Logistics
- Maintenance
- Metal steel
- Paper Industries
- Services
- Telecoms
- Transportation
- Utilities

Product Use  
Handling sharp parts in a dry or greasy environment.

## Features & Benefits

### Feature

Knitted glove in dyneema polyamide and composite fiber.  
 Grey PU coating on palm  
 Color: White  
 Gauge 13  
 Length: 25 cm.

### Benefit

#### COMFORT

The knitting technique helps to obtain a glove that conforms snugly to the hand, with good dexterity.

The glove offers maximum comfort and added sturdiness.

The cool Dyneema® touch gives an added sensation of comfort.

The tight knit (gauge 13) gives the glove perfect support, limits the penetration of dirt and offers a good touch.

The glove's ventilated back optimises its breathability.

#### RESISTANCE

The Dyneema®/lycra® thread provides outstanding properties against cuts.

The polyurethane coating at the palm and fingertips provides outstanding abrasion resistance.

The composite fiber fully protected by polyamide increase the cut resistance.

Caution! Do not expose this glove to the heat.

#### HYGIENE

Its white colour enhances the glove's hygiene and cleanliness.

Its grey coating enables work in a slightly soiled environment.

## Technical Description

### Description

CE CATEGORY : II Intermediary risks

In accordance with standards :

EN 420-2003 EEC Basic standards

EN 388-2003 Mechanical hazards

CHARACTERISTICS : Knitted glove in dyneema polyamide and composite fiber.

Grey PU coating on palm.

Color: White

Gauge 13.

Length: 25 cm.

### Product Technology

Knitted Coated

### Gauge

13

### Glove/liner color

White and grey

### Coating Type

Dyneema® / polyamide / composite fiber and lycra®

### Length

23,5 cm

### Harmlessness

In conformity with the European standards

### Dexterity

Class 5

**Sizes**

6 to 11

## EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	4
Cutting resistance	5
Tear resistance	4
Puncture resistance	3

## Packaging Label


**Tagging**

CE HONEYWELL

2132545 XX

EN 420

EN 388 : 4543

**Certifications** **E.C. Declaration of Conformity****EC Category PPE**

2

**Quality Assurance**

ISO 9001 / 2000

**EC Certificate Number**

Waitig for certification number

**EC Attestation****Photos & Images**<http://www.honeywellsafety.com/>**Additional Information****User Manual**

UI 102

**User Information Sheet**

102

**Maintenance**

**Storage Information**

Minimum packaging 10 pairs.  
Cartons of 100 pairs.

**Care Instructions**

This article can be cleaned. For cleaning instructions, please contact Honeywell safety products



[View other region sites](#)  
© 2013 Honeywell International Inc.



## E.C. Declaration of Conformity

**The manufacturer or its legal representative supplier in the European Community:**  
Honeywell Safety Europe

**Declares that the Personal Protective Equipment described here after conforms to the provisions of the European Council Directive 89/686/CEE:**

Designation: FLEXIDYN

Reference: 2132545

Standard(s): EN 388, EN 420

**This PPE is the object of the below EC examination certificate n°:**

Waitig for certification number

**Delivered by:**

CENTRE TECHNIQUE DU CUIR

4 rue Hermann Frenkel


69367

Lyon Cedex 07

Drawn up in Roissy, on the 15/07/2013

**By:** Eric Puille

**Division:** Gloves



ZI Paris Nord II 33, rue des Vanesses BP 50288 95958 Roissy CDG France

Tel: +33 (0) 49 90 79 79 Fax: +33 (0)1 49 90 79 80

[www.honeywellsafety.com](http://www.honeywellsafety.com)