



Commercial name

JALACCOLON S3 SRC

Production code

JMI02

Sizes

39 - 47



UPPER	Water-repellent full grain leather
LINING	3D.Lining. Three dimensional foam structures incorporated within a honeycombed architecture for greater ventilation
INSOLE	Confort-Tech: anatomic, antibacterial, shock absorber in the heel area
TOE CAP	Aérane-Tech 200J. Perforated toe cap for perfect foot ventilation. 100% composite. Non-magnetic, lightweight
ANTIPERFORATION MIDSOLE	FleXtane™ HP, made of textile composite materials, it protects 100% of the support surface of the foot and it can't be detected by metal detectors. It weigh 60 grams less versus a traditional steel insole
SOLE	Softane™ dual density PU with progressive heel shock absorber

Softane™
Prestige



	EN ISO 20345:2004		RESULTS
UPPER	REQUIREMENTS		
Water Vapour Permeability	mg/cmq h	≥ 0,8	2,7
Water Vapour Coefficient	mg/cmq	≥ 15	29,6
LINING			
Water Vapour Permeability	mg/cmq h	≥ 2	5,9
Water Vapour Coefficient	mg/cmq h	≥ 20	50,1
TOE CAP			
Impact resistance	mm	≥ 14	16
Compression resistance	mm	≥ 14	16
Antiperforation midsole			
Penetration resistance	N	≥ 1100	1200
Antistatic footwear			
Wet	MΩ	≥ 0,1	168
Dry	MΩ	≤ 1000	360
SOLE			
Abrasion resistance	mm ³	≤ 150	58
Flexing resistance	mm	≤ 4	2
Resistance to Fuel Oil	%	≤ 12	1
Energy absorption of seat region	J	≥ 20	24,3
Slip resistance on steel ground with glycerine	Heel	≥ 0,13	0,21
	Flat	≥ 0,18	0,21
Slip resistance on ceramics ground with detergent	Heel	≥ 0,28	0,28
	Flat	≥ 0,32	0,33

The data indicated in this sheet can be modified without notice following evolution in materials and products.
Jal Group. All rights reserved. All other products and companies names are marks or registered marks of their owners.
No part of this sheet can be reproduced in any form or mean, for no use, without written acceptance by Jal Group.