



Commercial name	PAOLA
Production code	JJD25
Safety Category	SB E A SRC
Sizes	35 - 42
UPPER	Perforated full grain leather
LINING	Leather
FUSSBETT	Full grain leather
TOE CAP	Classic steel 200J
SOLE	J-active made of Softane tm /PU



	<i>Standard requirements</i>		<i>Result</i>
	<i>EN ISO 20345:2007</i>		
UPPER			
Water Vapour Permeability	mg/cm ² h	≥ 0,8	2,1
Water Vapour Coefficient	mg/cm ²	≥ 15	27,9
LINING			
Water Vapour Permeability	mg/cm ² h	≥ 2	5,3
Water Vapour Coefficient	mg/cm ² h	≥ 20	44,5
TOE CAP			
Impact resistance	mm	≥ 14	14
Compression resistance	mm	≥ 14	14
Antistatic footwear			
Wet	MΩ	≥ 0,1	35
Dry	MΩ	≤ 1000	155
SOLE			
Abrasion resistance	mm ³	≤ 150	135
Flexing resistance	mm	≤ 4	3,5
Resistance to Fuel Oil	%	≤ 12	0,7
Energy absorption of seat region	J	≥ 20	40
Slip resistance on steel ground with glycerine	Tacco	≥ 0,12	0,21
Slip resistance on ceramics ground with detergent	Piano	≥ 0,16	0,29
	Tacco	≥ 0,28	0,30
	Piano	≥ 0,32	0,40

The data indicated in this sheet can be modified without notice following evolution in materials and products.
Jal Group. All rights reserved. All other products and companies names are marks or registered marks of their owners.
No part of this sheet can be reproduced in any form or mean, for no use, without written acceptance by Jal Group.