

# TECHNICAL DATA SHEET

**STAN S3 HI No. 8651**

**Sz. 39 - 50**



## LABELLING ACCORDING TO STANDARD

Standard for footwear protecting against thermal risks and splashes of molten metal EN ISO 20349 S3 (supplement to EN ISO 20345)	Basic requirement for S3: <b>A</b> Antistatic shoe - <b>E</b> Energy absorption in the heel - <b>FO</b> Fuel resistance - <b>WRU</b> Water penetration and water absorption resistant upper - <b>P</b> Penetration resistance - Closed heel area - Profiled outsole
Additional requirements	<b>SRC</b> Slip resistance: Slip resistant on floors of ceramic tiles with a sodium lauryl sulfate (SLS) solution and on steel floors with glycerol. When it comes to slip resistance as defined by EN ISO 20345, SRC signifies the best possible rating a safety shoe can reach.  <b>AI</b> RESISTANT TO MOLTEN ALUMINIUM  <b>Fe</b> RESISTANT TO MOLTEN IRON  <b>HI</b> HEAT INSULATED  <b>HRO</b> HEAT RESISTANT OUTSOLE Heat resistance against contact heat, also during short-term high temperatures


## FORM

Safety pull-on boot  	Form C - in size 42, the upper height must be at least 17.8 cm.
-----------------------------	---

## AREAS OF APPLICATION

Areas of application	<p>Indoors and outdoors</p> <p>Areas where exposure to moisture is expected (S2)</p> <p>Areas where there is a risk of penetration from pointed and sharp objects (S3)</p> <p>Hot zones where high demands are placed on the sole for heat resistance E.g. foundries, welding works etc.</p> <p>Areas where there is a risk of molten iron splashes</p> <p>Areas where there is a risk of molten aluminium splashes</p>
----------------------	---

## FEATURES

Certification in accordance with DGUV rule 112-191	<ul style="list-style-type: none"> <li>Certified for orthopaedic inserts</li> </ul> 
Collar padding	<ul style="list-style-type: none"> <li>Excellent wearing comfort: the ankle-wrapping, softly padded upper edge provides for stability and grip in the shoe.</li> </ul>
High boot without laces or zippers	<ul style="list-style-type: none"> <li>Quick getting in and out</li> </ul>
Quick release fastener	<ul style="list-style-type: none"> <li>Allows shoe to be removed with one hand in the case of danger</li> </ul>
Seams made of heat-resistant thread	<ul style="list-style-type: none"> <li>Best possible protection against flames, heat and chemicals. Cleaning does not affect the heat resistance.</li> </ul>


## UPPER MATERIAL

Cowhide leather - fire-resistant	<ul style="list-style-type: none"> <li>Areas of application S2/S3</li> <li>Natural material</li> <li>Wear-resistant</li> <li>Breathable</li> <li>Water penetration/absorption in accordance with EN ISO 20345 S2</li> </ul>
----------------------------------	---

## LINING

Leather lining	<ul style="list-style-type: none"> <li>High tear resistance</li> <li>Breathable</li> <li>Natural material</li> </ul>
Heel pocket lining	<ul style="list-style-type: none"> <li>The abrasion-resistant microfibre material is particularly sturdy and provides for a pleasant wearing comfort.</li> </ul>

## TOE PROTECTION CAP

<p>Steel toe cap</p> 	<ul style="list-style-type: none"> <li>Protection against impacts of min. 200 joules and pressure loading of min. 15 kN</li> <li>Permanent edge coverage for cushioning</li> <li>Ergonomically shaped</li> <li>Comfortable toe room</li> <li>Good coverage of the little toe area</li> </ul>
--	--

## INLAY SOLE

Full-length inlay sole made of fleece



- Needled with aluminium foil for an improved heat preservation
- The full-length, exchangeable inlay sole provides the highest possible comfort in safety shoes.
- The inlay sole is functionally absorbing and releasing moisture and thus provides for a pleasant foot climate.
- Antistatic

## PENETRATION RESISTANCE

Metal-free penetration protection

The textile midsole complies with the penetration safety standard EN 12568 and furthermore fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345. The light and flexible material enables an increased elasticity of the shoe, which can particularly be recognized when working on uneven grounds or on your knees.

The textile variant offers 100 % foot coverage compared to steel midsoles (foot coverage 85 % due to limits in the shoe manufacturing process). Being 100 % metal-free and antimagnetic, this equipment is used as penetration protection in safety shoes.

## OUTSOLE

STEINAU mono-density tread sole with profile



- Excellent slip resistance
- Antistatic

Outsole: Rubber

- Colour: black
- Profile depth: 6.0 mm
- Particularly abrasion-resistant
- Heat-resistant to approx. 200°C, for short periods to 300°C
- Flexible at cold temperatures to approx. -20°C
- Oil and fuel resistant
- Resistant to a large number of chemicals (acids and alkalis)
- Notch-resistant