



Featuring Nomex®, a high-performance fiber for high burning protection.

TEGERA® ARC FLASH 2010



[Learn more](#)

HIGH PROTECTION FOR ARC FLASH HAZARDS

The Arc Flash glove features Nomex®, a high-performance fiber renowned for high burning protection. Withstands up to 11 cal/cm², Arc category level 2. In addition to Arc Flash protection, the glove contains Kevlar® and therefore offers high-level cut resistance (E). Neoprene dipping on palm. The glove withstands contact heat up to 100°C/212°F and are flame retardant.

CHARACTERISTICS

- High level of protection

FUNCTIONS

- Withstands contact heat up to 100°C
- Flame retardant
- Heat-resistant

Nomex®

PREVENTS RISK OF

Burn injuries, Heat injuries, Cut injuries, Grazes, Scratches, lacerations, Contact with dirt

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, Warm environments, Environments with explosive risks

PRIMARY AREAS OF USE

Construction, Electric power work, Electrical installation, Hot work

PRIMARY INDUSTRIES OF USE

Mining, Oil, gas, petrochemical, Life science and electronics, Metal fabrication, Machinery and equipment, MRO, Utilities, Building and construction, Facilities

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Arc flash protection gloves, Cut resistant gloves, Heat protection gloves

CATEGORY Cat. III

COLLECTION Arc Flash

KNITTING GAUGE (GG) 13

LINING MATERIAL Glass fibre thread, KEVLAR® fiber, Modacrylic, Nomex®, Spandex

LENGTH 220-260 mm

DEXTERITY 5

GRIP DESIGN Foam grip pattern

COLOUR Black

PAIRS PER: BUNDLE/CARTON 12/60

DISPLAY TYPE Hook with hangtag

DIPPING Palm-dipped

DIPPING MATERIAL Neoprene

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

CUT RESISTANCE (EN ISO 13997) Cut resistance level E

CUT RESISTANCE (EN ISO 13997) TDM: 23.2N

INNER MATERIAL SPECIFICATION Meta-aramid, Para-aramid, Glass fibre thread, Modacrylic, Elastane

OUTER MATERIAL SPECIFICATION Chloroprene

COMPLIANCE



TP TC 019:2011

EN ISO 21420:2020



EN 388:2016+A1:2018 3X41E



EN 407:2020 4131XX



ASTM F2675-23 ATPV=11 CAL/CM²



Contact heat rating valid for palm area only

FEATURES



Cut protection

SIZE		ARTICLE NUMBER	EAN
10	XL	2010-10	7340118492322
11	XXL	2010-11	7340118492476
6	XS	2010-6	7340118491721
7	S	2010-7	7340118491875
8	M	2010-8	7340118492025
9	L	2010-9	7340118492179

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com