

TEGERA® 8150

Chemical protection glove, 0,40 mm latex, diamond grip pattern, flock-lined, Cat. III, yellow, approved for handling foodstuffs, waterproof

PROPERTIES

Flexible, good grip, good fit, comfortable

SPECIFICATION

TYPE OF GLOVE Disposable and/or chemical resistant gloves

CATEGORY Cat. III

SIZE RANGE 7, 8, 9, 10

MATERIAL Latex

THICKNESS 0,40 mm

INSIDE Flock-lined

DEXTERITY 5

GRIP PATTERN Diamond grip pattern

LENGTH RANGE 300 mm

COLOUR Yellow

PAIRS PER PACKAGE/CARTON 10/100

AQL 0.65

DISPLAY Bag with euro slot



SIZE	ART. NO.	EAN NO.
7	8150-7	7392626815063
8	8150-8	7392626815070
9	8150-9	7392626815087
10	8150-10	7392626815094

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 8150

FEATURES

Splash protection against chemicals, approved for handling foodstuffs

PRIMARY PROTECTION

Prevents risk of: contact with moisture, contact with damp

PRIMARY ENVIRONMENTS OF USE

Wet environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Chemical work, chemical technology work, laboratory work, sanitation, cleaning, kitchen work, care work, service work

PRIMARY INDUSTRIES OF USE

Agriculture, chemical, service

TYPE OF WORK

Medium weight

2(4)

CE 0321 Cat. III



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-03-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 8150

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

CHEMICAL RESISTANCE

According to EN 374-3. For details, please contact Ejendals

COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

Council directive 89/686/EEC (PPE Directive)

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to wear (No. of revolutions)	1	(4)
B) Resistance to cutting (Index)	0	(5)
C) Tear resistance (Newton)	1	(4)
D) Puncturing resistance (Newton)	0	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).


Level of protection	1	2	3	4	5
A) Resistance to wear (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 374-2:2003 Protective gloves against chemicals and micro-organisms - Part 2: Determination of resistance to penetration

EN 374-3:2003 Protective gloves against chemicals and micro-organisms - Part 3: Determination of resistance to



CE 0321 Cat. III



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-03-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 8150

permeation by chemicals

Permeation levels are based on breakthrough times as follows

Permeation level	1	2	3	4	5	6
Minimum breakthrough times (min)	10	30	60	120	240	480
Definition of breakthrough time through the glove palm (Lugm/cm ² /min)						

K: Sodium hydroxide 40% (CAS number 1310-73-2) - Permeation level 6

L: Sulphuric acid 96% (CAS number 7664-93-9) - Permeation level 2

Suitable for contact with foodstuffs

4(4)



CE 0321 Cat. III



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-03-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com